

CLARE FIRE DEPARTMENT

FIRE APPARATUS SPECIFICATIONS

CUSTOM PUMPER

CLARE FIRE DEPARTMENT

Y__N__

INTENT OF SPECIFICATIONS

It is the intent of these specifications to cover the furnishing and delivery to the **Clare Fire Department** of a complete fire apparatus equipped as hereinafter specified. With the view of obtaining the best results and the most acceptable apparatus for service, these specifications cover only the general requirements as to the type of construction and tests to which the apparatus must conform, together with certain details to furnish equipment and appliances with which the successful bidder must conform. Minor details of construction and materials, where not otherwise specified, are left to the discretion of the contractor who shall be solely responsible for the design and construction of all features. The NATIONAL FIRE PROTECTION ASSOCIATION pamphlet #1901 current edition for Motor Vehicle Apparatus, unless otherwise specified in these specifications shall prevail.

ONLY THE SPECIFIED FIREFIGHTING SUPPORT EQUIPMENT LISTED IN THESE SPECIFICATIONS SHALL BE PROVIDED.

The apparatus shall conform to all Federal motor vehicle safety standards.

Bids will only be considered from companies that have an established reputation in the field of fire and/or rescue apparatus manufacturing.

Each bid must be accompanied by a set of detailed contractors specifications consisting of a detailed description of the apparatus and equipment proposed. These specifications shall include size, location, type, and model of all component parts being furnished. Detailed information shall be provided on the materials used to construct all facets of the apparatus body. Any bidder who fails to submit detailed construction specifications shall be considered non-responsive and shall render their proposal ineligible for award.

Each bidder shall furnish a computer generated weight and balance analysis for the unit being proposed. It shall address individual and combined axle weights and include an analysis on the vehicle's center of gravity. It shall also include a figure for excess payload capacity. Any bidder who fails to submit the weight and balance analysis in this format shall be considered non-responsive and shall render their proposal ineligible for award.

Each bidder shall furnish satisfactory evidence of the ability to construct the apparatus specified, and shall state the location of the factory where the chassis and apparatus will be built. They shall also show that they are in a position to render prompt service and to furnish replacement parts for the completed apparatus chassis, body and components.

The manufacturer shall specify in his bid the number of working days and/or calendar days after acceptance of the formal contract by the manufacturer that the completed apparatus will be delivered by the purchaser. The manufacturer will not be held liable for changes arising from its failure to make or delay in making deliveries because of fire, flood, riot, major component shortage, accidents, acts of God, or any circumstances beyond their control.

QUALITY AND WORKMANSHIP

The workmanship must be of the highest quality in its respective field. Special consideration will be given to the following points:

CUSTOM PUMPER

CLARE FIRE DEPARTMENT

1. Accessibility of the various components which require periodic maintenance or monitoring
2. Ease of vehicle operation (pumping and driving)
3. Visibility for the driver
4. Symmetrical proportions

Construction must be rugged and design must be certified to carry the loads as specified and to meet the road and speed requirements as set forth under "PERFORMANCE TESTS AND REQUIREMENTS" of NFPA Pamphlet #1901 current edition.

Welding shall not be employed in the assembly of the apparatus in a manner that will prevent the removal of major components for service and/or repair.

DESIGN

The successful bidder shall be solely responsible for the design, construction and material used in the construction of the vehicle. The apparatus shall be of the latest design and type while using the most current industry construction techniques.

Each bidder shall supply with their bid a detailed drawing consisting of the driver side, passenger side and rear views of the apparatus. This drawing shall be representative of the apparatus being bid. The drawing must include but not be limited to all principle dimensions (height/width/length). Pictures or brochures are also encouraged that represent the quality of construction being proposed.

The apparatus, assemblies, component parts, etc., shall be designed and constructed with consideration to the nature and distribution of the load to be sustained and to the general character of the service to which the apparatus is to be subjected.

The apparatus shall be designed with great consideration given to overall vehicle weight and weight distribution. A computerized weight distribution calculation shall be included with the bid. A calculation shall include the chassis weight with all fluids and fuels topped off, estimated body weight, a 250-lb. allowance per seat for personnel and a 2,500 lb. distributed load allowance for equipment. Any bidder who fails to submit weight and balance calculations shall be considered non-responsive and shall render their proposal ineligible for award.

The apparatus shall be designed and constructed so component parts can be removed for service and repair with standard tools. Any special tools needed to service any component of the apparatus built or supplied by the component manufacturer shall be supplied with the apparatus. During the design and construction the apparatus manufacturer shall take into consideration the ease of access to various areas requiring lubrication, inspection, service or adjustment.

The design and materials must be of the highest quality in its respective field. Quality control inspections shall be performed at each step of the manufacturing process.

The manufacturer shall meet the minimum requirements of NFPA Pamphlet 1901 current edition, The Underwriter's Laboratories, Inc. and all State and Federal Department of Transportation vehicle regulations at the time of the bid for this apparatus.

ROAD TEST

All road tests will be performed per NFPA Pamphlet #1901 current edition requirements.

CLARE FIRE DEPARTMENT

LIABILITY

The successful bidder shall defend any and all suits and assume all liability for use of any patented process, device or article forming a part of the cab and chassis, or any appliance under the contract.

DELIVERY and/ DELIVERY DATA REQUIRED

1. The completed apparatus shall be delivered to the Clare Fire Department.
2. The successful bidder's representative shall remain at the Fire Department until released by the Fire Chief or Commission during which time he shall instruct Fire Department personnel in the proper operation, care and maintenance of the complete apparatus.

Information required at time of delivery to be supplied by the manufacturer:

- A. Manufacturer's statement of origin
- B. Electrical "as built" schematic booklet
- C. Final build data sheet showing serial numbers for the following:
 1. Cab and chassis VIN
 2. Engine serial number
 3. Transmission serial number
 4. Apparatus/Body serial number
- D. One copy of a complete operations and general maintenance instructions as delivered, including but not limited to the chassis, engine, transmission, axles, lubrication charts, rescue body and appropriate accessories.
- E. The Underwriters Laboratories Incorporated test Certification shall be provided on delivery of the apparatus.
- F. The successful bidder shall supply all data required in NFPA Pamphlet #1901 current edition chapter 14 -20.

EXCEPTIONS TO SPECIFICATIONS

Each bidder response shall include a returned copy of this Request for bid with the yes/no columns checked for compliance to specifications.

All exceptions, no matter how minor must be marked in the "NO" column.

Those exceptions shall be listed on a separate sheet and shall refer to specification page number and paragraph. It will be mandatory for any perspective bidder that deviates from the proposed specifications, to give a full description of all deviations.

Bidder and his/her manufacturer being represented will be held responsible for deviations not specifically addressed or approved by the Fire Department. Items not addressed will be considered as being bid with no exception and will be included on the apparatus in the

CLARE FIRE DEPARTMENT

form presented in our specifications. Non-compliance will be grounds for rejection of the completed vehicle - **NO EXCEPTION.**

Failure to follow this method will add a considerable time to the bid review process and may be cause for rejection of the bid.

The purchaser will not consider proposals or demonstrators taking total exception to the bid specifications.

Where bidder's specifications and/or construction differ in any way from the bid specification, a full and complete description in the specification will be required. Drawings will also be required to show alternative construction methods. Partial descriptions or general clarifications covering groups or sections of the specifications will be unacceptable.

CLARIFICATIONS TO SPECIFICATIONS

Clarifications shall refer to specification page number and paragraph. Any such clarification that appears vague or misleading shall be considered an exception. Complete clarifications are required describing the reason for the deviation. Apparatus will be inspected upon delivery for compliance with specifications.

CONTRACT AWARD

The purchaser reserves the right to reject any or all bid proposals and purchase the equipment it deems most suitable to its needs. Since all components and materials are commercially available these specifications shall in no way be considered proprietary.

Price shall be based on payment upon receipt of the completed apparatus by the purchaser. No discounts or prepayment schedules shall be listed on the proposal page. All bidders are required to detail any payment terms for the apparatus and these terms shall be listed on a separate page entitled OPTIONS. These options may or may not be considered at the discretion of the purchaser.

All bids shall remain valid for 30 days after opening.

PAYMENT TERMS

The Purchaser agrees to purchase the apparatus and miscellaneous equipment pursuant to the following terms and conditions:

1. All prices shall be less any taxes.
2. The final payment for the apparatus shall be paid upon delivery and acceptance by the fire department per enclosed payment terms. An invoice shall be presented on or before delivery of the apparatus. Apparatus review shall be provided prior to acceptance.
3. The apparatus, without exception, shall not be placed "In Fire Service" prior to full payment of apparatus.

SUBMISSION OF BIDS

Bids shall be submitted in accordance with the following instructions:

CLARE FIRE DEPARTMENT

1. The bidder's proposed specifications shall be provided in full. Any deviations and clarifications shall be clearly marked.

2. The bidder's proposed specifications detailing their construction methods shall be provided.

This is necessary to evaluate each bidder's actual intent of building the equipment as specified herein.

The bidder's proposed format shall be the same as these specifications to allow the customer to easily compare the bids; NO EXCEPTIONS.

Bids are to be submitted in the same order as our specifications; NO EXCEPTIONS.

3. Bids shall be returned in a sealed envelope clearly marked "BID FOR FIRE APPARATUS".

4. The purchaser reserves the right to accept or reject any and all bids, to waive irregularities and to make the award in any manner deemed to be in their best interest.

Y__N__

NFPA REQUIRED ITEMS

The purchaser shall be responsible for providing all equipment items required by NFPA pamphlet that are not otherwise indicated or addressed in these specifications.

Y__N__

SINGLE SOURCE BODY BUILDER AND CONSTRUCTION

The apparatus manufacturer shall be the prime (single source) builder of this severe duty all aluminum fire apparatus quality body.

All engineering, design, fabrication, testing, paint and finish shall take place at the apparatus manufacturer's privately owned top tiered manufacturing facility.

Bodies that are mass produced from lower quality materials such as thin stamped utility style designs, bolted together designs or those that are manufactured by a third party for the apparatus manufacturer shall be considered sub-standard and shall not be acceptable for this project.

The body shall be designed and manufactured entirely from formed and welded aluminum plate and aluminum extrusions to ensure a high quality design and finish that shall provide years of uninterrupted service. Bodies that incorporate steel as structural support or that utilizes steel in any way shall be considered sub-standard and shall not be acceptable for this project. **NO EXCEPTIONS**

Y__N__

CONSTRUCTION DRAWINGS

A basic drawing will be included with the proposal. Upon award a fully detailed drawing will be supplied to the Fire Department. The drawing shall be signed and returned to the manufacturer and kept on file for future reference.

CLARE FIRE DEPARTMENT

Y__N__

SERVICE CENTER

The selling dealer or manufacturer shall have a full service center. The bidder must provide detailed information and the location of the service center.

To insure full support for service after the sale, the selling dealer and/or manufacturer shall be capable of providing full factory service when required for the cab and chassis, pump, tank and miscellaneous body components. The service center must have state repair facility, mechanic and dealer licenses.

Service centers must have a staff of factory-trained EVT Certified mechanics available, well versed in all aspects of service for all major components of the apparatus.

Service centers must have 24 hour support and a minimum of two (2) fully equipped service vehicles.

Y__N__

PRECONSTRUCTION CONFERENCE

The prime contractor will have a Pre-Construction Conference prior to any manufacturing. The purpose of meeting is to finalize all construction details. A final drawing shall be provided at the pre-construction meeting.

The location shall be at the manufacturing facility. All expenses for transportation, lodging and meals are paid for by the bidder. Trips in excess of 250 miles each way will be made by commercial air. The selling dealer and/or representative will be present at the pre-construction conference.

Y__N__

INSPECTION TRIPS

Two (2) inspection trips for **five (5)** customer personnel will be arranged with all expense for transportation and meals paid for by the dealer. Transportation will be by motor vehicle unless otherwise indicated in the proposal. Trips in excess of 250 miles each way will be made by commercial air.

Timing of the trips shall be coordinated between the customer and selling dealer.

Pre-Construction
Final Inspection

Y__N__

PROGRESS PICTURES

Progress pictures will be provided once body has started construction. Pictures will be provided throughout each phase of construction, paint and assembly.

CLARE FIRE DEPARTMENT

DELIVERY

Y__N__

The completed apparatus will be delivered under its own power to the Clare Fire Department. A factory delivery technician will accompany the apparatus.

Apparatus review will be provided by an authorized representative of the manufacturer as prescribed by the customer.

SEATING CAPACITY PLATE

Y__N__

A permanent plate indicating seat belt use and occupancy shall be installed in a visible location.

HELMET WARNING PLATE

Y__N__

A permanent plate stating "DO NOT WEAR HELMET" shall be installed in a visible location.

FLUID CAPACITY PLATE

Y__N__

A permanent plate listing all fluids and capacities shall be installed in a visible location.

OVERALL HEIGHT PLATE

Y__N__

A plate indicating overall height, overall length, overall width and the vehicle GVRW shall be installed in a location visible to driver.

TAILBOARD PLATE

Y__N__

A permanent plate shall be installed at the rear indicating "DO NOT RIDE ON REAR STEP".

CLARE FIRE DEPARTMENT

CUSTOM CHASSIS

Alternate brands of custom chassis will be accepted as long as they meet or exceed the following specifications.

Y__ N__

MODEL

The chassis shall be a Metro Star model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

Y__ N__

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2022 or newest current model year.

Y__ N__

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

Y__ N__

CAB AND CHASSIS LABELING LANGUAGE

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English. All applicable caution, warning, and safety notice labels shall be Innovative Controls brand. Where applicable to the location within the specific layout and label package of the cab and chassis, the labels shall include decorative chrome bezels. Designs shall include bezels that fit individual labels or packaged configurations of labels in certain common locations.

The following labels shall be Innovative Controls brand, each including a decorative chrome bezel (where applicable):

- Shoreline
- Aerial Stowed
- Aerial Breakers 2
- Air Conditioner
- Cab Tilt Plate
- Air Compressor Breaker
- Battery Conditioner Breaker
- Helmet Caution
- Horn Tag
- Q2B Tag

CUSTOM PUMPER

CLARE FIRE DEPARTMENT

- Load Center Plate
- Not a Step Label
- Occupancy Tag
- Do Not Move
- Occupants Must Be Seated
- Do Not Stand
- Danger Do Not Weld
- Danger--Untrained Operator
- Def Tag, including any additional labels selected in the 2907- subcat
- Battery Direct
- Kneeling
- IFS Air Fault
- Engine Brake
- Retarder
- LR 100 Amp Node
- 300 Amp EPU
- 100 Amp Front O/R Node
- 100 Amp T/T Node
- 100 Amp RR O/R Node
- 10 Amp EPU
- Master Power
- 12 Volt Power
- Aerial Hours
- Pump In Drive

Windshield Washer Fluid

Y__ N__

APPARATUS TYPE

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

Y__ N__

VEHICLE TYPE

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

Y__ N__

VEHICLE ANGLE OF APPROACH PACKAGE

The angle of approach of the apparatus shall be a minimum of 8.00 degrees.

NFPA1901 Angle of Approach definition:

“To determine the angle of approach, place a thin steel strip against the front of the tires where they touch the ground or stretch a tight string from one front tire to the other at the front where they touch the ground. Determine the lowest point (component or equipment) on the vehicle forward of the front tire that would make the smallest angle of approach. Hang a plumb bob from the lowest point and mark the point on the ground where the point of the plumb bob touches. Measure the vertical distance from the ground to the

CUSTOM PUMPER

CLARE FIRE DEPARTMENT

point where the plumb bob was hung (distance V). Measure the horizontal distance from the plumb bob point to the steel strip or string running from front tire to front tire (distance H). Divide the vertical distance by the horizontal distance. The ratio of V/H is the tangent of the angle of approach. If the ratio is known, the angle of approach can be determined from a table of trigonometric functions of angles or from a math calculator. The standard requires a minimum angle of approach of 8.00 degrees: since the tangent of 8.00 degrees is 0.1405, if V divided by H is 0.1405 or larger, the angle of approach is 8.00 degrees or greater.”

Y__ N__

AXLE CONFIGURATION

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

Y__ N__

GROSS AXLE WEIGHT RATINGS FRONT

The front gross axle weight rating (GAWR) of the chassis shall be 20,000 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

Y__ N__

GROSS AXLE WEIGHT RATINGS REAR

The rear gross axle weight rating (GAWR) of the chassis shall be 30,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

Y__ N__

PUMP PROVISION

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location. Chassis driveline pump provisions shall include an interlock feature for automatic setting of the park brake when the vehicle is shifted into pump mode while the transmission is in neutral and the transmission output speed translates to less than 1 mph. When the conditions are met the driver side parking brake valve shall activate. Once shifted to road mode the condition for electric automatic brake engagement is no longer present and the driver's parking brake control valve shall function normally.

Y__ N__

WATER & FOAM TANK CAPACITY

The chassis shall include a carrying capacity of 750 gallons (2839 liters) to 1250 gallons (4732 liters). The water and/or foam tank(s) shall be supplied and installed by the apparatus manufacturer.

CLARE FIRE DEPARTMENT

Y__ N__

CAB STYLE

The cab shall be a custom, fully enclosed, MFD model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This cab shall include six (6) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 131.10 inches with 54.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner in the non-raised roof area and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 51.88 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for

CLARE FIRE DEPARTMENT

personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

Y__ N__

OCCUPANT PROTECTION

The vehicle shall include the Advanced Protection System™ (APS) which shall secure belted occupants and increase the survivable space within the cab. The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The system components shall include:

- Driver steering wheel airbag
- Driver dual knee air bags (patent pending) with energy management mounting (patent pending) and officer knee airbag.
- Large driver, officer, and crew area side curtain airbags
- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around the occupants, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries
- Heavy truck Restraints Control Module (RCM) - receives inputs from the outboard sensors, selectively deploys APS systems, and records sensory inputs immediately before and during a detected qualifying event
- Integrated outboard crash sensors mounted at the perimeter of the vehicle - detects a qualifying front or side impact event and monitors and communicates vehicle status and real time diagnostics of all critical subsystems to the RCM
- Fault-indicating Supplemental Restraint System (SRS) light on the driver's instrument panel

Frontal impact protection shall be provided by the outboard sensors and the RCM. In a qualifying front impact event the outboard sensors provide inputs to the RCM. The RCM

CLARE FIRE DEPARTMENT

activates the steering wheel airbag, driver side dual knee airbags (patent pending), officer side knee airbag, and advanced seat belts for each occupant in the cab.

Rollover, side impact, and ejection mitigation shall be provided by the outboard sensors and the RCM. In qualifying rollover or side impact events the outboard sensors provide inputs to the RCM. The RCM activates the side curtain airbags and advanced seat belts for each occupant in the cab. The RCM measures roll angle, lateral acceleration, and roll rate to determine if a rollover event or side impact event is imminent or occurring.

In the event of a qualifying offset or other non-frontal impact, the RCM shall determine and intelligently deploy the front impact protection system, the side impact protection system, or both front and side impact protection systems based on the inputs received from the outboard crash sensors.

Y__ N__

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

Y__ N__

FRONT GRILLE

The front fascia shall include a box style, 304 stainless steel front grille 44.45 inches wide X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 732.00 square inches. The upper portion of the grille shall be hinged to provide service access behind the grille.

Y__ N__

CAB UNDERCOAT

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

Y__ N__

CAB SIDE DRIP RAIL

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

Y__ N__

CAB PAINT EXTERIOR

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

CLARE FIRE DEPARTMENT

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper followed by sealing the seams with SEM brand seam sealer.

The cab shall then be painted the specific color designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene. The paint shall have a minimum thickness of 2.00 mils, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

CAB PAINT MANUFACTURER

Y__ N__

The cab shall be painted with PPG Industries paint.

CAB PAINT PRIMARY/LOWER COLOR

Y__ N__

The primary/lower paint color shall be:

CAB PAINT SECONDARY/UPPER COLOR

Y__ N__

The secondary/upper paint color shall be:

CAB PAINT EXTERIOR BREAKLINE

Y__ N__

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 1.00 inch below the door windows on each side of the cab. The breakline shall curve down at the front cab corners to approximately 5.00 inches below the windshields on the front of the cab.

CAB PAINT PINSTRIPE

Y__ N__

Where the upper and lower paint colors meet a temporary 0.50 inch wide black pinstripe shall be applied over this break line to offer a more finished look prior to the final pinstripe being installed by the OEM.

CLARE FIRE DEPARTMENT

CAB PAINT WARRANTY

Y__ N__

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

The warranty details can be found in the chassis warranty document.

CAB PAINT INTERIOR

Y__ N__

The visible interior cab structure surfaces shall be painted with an easy-to-clean gray texture finish.

CAB ENTRY DOORS

Y__ N__

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

CAB ENTRY DOOR TYPE

Y__ N__

All cab entry doors shall be full length in design to fully enclose the lower cab steps. Entry doors shall include Pollak mechanical plunger style switches for electrical component activation.

CAB INSULATION

Y__ N__

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

CAB STRUCTURAL WARRANTY

Y__ N__

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY TERMS CAN BE FOUND IN THE CHASSIS WARRANTY DOCUMENT, WHICH CONTAINS THE COMPLETE STATEMENT OF THE WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

CLARE FIRE DEPARTMENT

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

Y__ N__

CAB TEST INFORMATION

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

Y__ N__

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

Y__ N__

MULTIPLEX DISPLAY

The multiplex electrical system shall include (2) Weldon Vista IV displays which shall be located one (1) on the right side of the dash in the switch panel and one (1) on the left side of the dash in the switch panel. The Vista IV displays shall feature full color LCD display screens which include a message bar displaying the time of day and important messages requiring acknowledgement by the user which shall all be displayed on the top of the screen in the order they are received. There shall be eight (8) push button virtual controls, four (4) on each side of the display for the on-board diagnostics. The display screens shall be video ready for back-up cameras, thermal cameras, and DVD.

The Vista IV displays shall offer varying fonts and background colors. The displays shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

Y__ N__

LOAD MANAGEMENT SYSTEM

The apparatus load management shall be performed by the included multiplex system. The multiplex system shall also feature the priority of sequences and shall shed electrical loads based on the priority list specifically programmed.

CLARE FIRE DEPARTMENT

Y__ N__

DATA RECORDING SYSTEM

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

Y__ N__

ACCESSORY POWER

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

Y__ N__

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

Y__ N__

ENGINE

The chassis engine shall be a Cummins L9 engine. The L9 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 450 horse power at 2100 RPM and shall be governed at 2200 RPM. The torque rating shall feature 1250 foot pounds of torque at 1200 RPM with 543 cubic inches (8.9 liters) of displacement.

The L9 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2021 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

CLARE FIRE DEPARTMENT

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CK-4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

Y__ N__

CAB ENGINE TUNNEL

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

Y__ N__

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

Y__ N__

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

Y__ N__

ENGINE HIGH IDLE CONTROL

The vehicle shall be equipped with a virtual Vista button and an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the engine is running and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indicator on the Vista display and control screen for the high idle speed control.

Y__ N__

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

Y__ N__

AUXILIARY ENGINE BRAKE

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS

CLARE FIRE DEPARTMENT

event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

Y__ N__

AUXILIARY ENGINE BRAKE CONTROL

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled via an off/low/medium/high virtual button on the Vista display and control screen. The multiplex system shall remember and default to the last engine brake control setting when the vehicle is shut off and re-started.

Y__ N__

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

Y__ N__

FLUID FILLS

The front of the chassis shall accommodate fluid fill for the engine oil through the grille. This area shall also accommodate a check for the engine oil. The transmission, power steering, and coolant fluid fills and checks shall be under the cab. The windshield washer fill shall be accessible through the front left side mid step.

Y__ N__

ENGINE DRAIN PLUG

The engine shall include an original equipment manufacturer installed oil drain plug.

Y__ N__

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

CLARE FIRE DEPARTMENT

Y__ N__

REMOTE THROTTLE HARNESS

An apparatus interface wiring harness for the engine and transmission pump interlocks shall be supplied with the chassis. The harness shall include a connector for connection to a chassis pump panel harness supplied by the body builder and shall terminate in the left frame rail behind the cab for connection by the body builder. The harness shall include circuits deemed for a pump panel and shall contain circuits for a hand throttle, and a multiplexed gauge. Separate circuits shall also be included for a pump control switch, "Pump Engaged" and "OK to Pump" indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, clean power, customer ignition, air horn solenoid switch, high idle switch and high idle indicator light. The harness shall contain interlocks that will prevent shifting to road or pump mode unless the transmission output speed translates to less than 1 mph and the transmission is in neutral. The shift to pump mode shall also require the park brake be set.

Y__ N__

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

Y__ N__

ENGINE PROGRAMMING IDLE SPEED

The engine low idle speed will be programmed at 700 rpm.

Y__ N__

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator. This ember separator shall be designed to protect the downstream air filter from embers using a combination of unique flat and crimped metal screens packaged in a heavy duty galvanized steel frame. This multilayered screen shall trap embers and allow them to burn out before passing through the pack.

The engine air intake system shall also include an air cleaner mounted above the radiator. This air cleaner shall utilize a replaceable dry type filter element designed to prevent dust and debris from being ingested into the engine. A service cover shall be provided on the housing, reducing the chance of contaminating the air intake system during air filter service.

The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

Y__ N__

ENGINE FAN DRIVE

The engine cooling system fan shall incorporate a thermostatically controlled, Horton fully variable type fan drive with SmartClutch J-1939 CAN controller.

CLARE FIRE DEPARTMENT

The variable speed fan clutch only engages at the amount needed for proper cooling to facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail-safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure. The fan speed shall include a J-1939 CAN clutch controller to receive signal from the engine control module to activate at variable rates of speed. Variable speeds shall be set through thermostatic and engine speed signals to run as efficiently and quietly as required to maintain temperature.

Y__ N__

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer fan with a three (3) piece fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and rearward oriented sight glass to observe coolant in the system. A cold fill and observation line shall be included within the frame mounted translucent recovery bottle to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

The radiator and charge air cooler shall be removable through the bottom of the chassis.

CLARE FIRE DEPARTMENT

ENGINE COOLING SYSTEM PROTECTION

Y__ N__

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame components.

ENGINE COOLANT

Y__ N__

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ELECTRONIC COOLANT LEVEL INDICATOR

Y__ N__

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

ENGINE PUMP HEAT EXCHANGER

Y__ N__

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

COOLANT HOSES

Y__ N__

The cooling system hoses shall be silicone heater hose and formed silicone coolant hoses with formed aluminized steel tubing. Bulkhead fittings shall be used where the heater hoses pass through the cab. All heater hose, silicone coolant hose, and tubing shall be secured with stainless steel constant torque band clamps.

ENGINE COOLANT OVERFLOW BOTTLE

Y__ N__

A remote engine coolant overflow expansion bottle shall be provided in the case of over filling the coolant system. The overflow bottle shall capture the expansion fluid or overfill rather than allow the fluid to drain on the ground.

CLARE FIRE DEPARTMENT

Y__ N__

ENGINE EXHAUST SYSTEM

The exhaust system shall include an end-in end-out horizontally mounted single module after treatment device, and downpipe from the charge air cooled turbo. The single module shall include four temperature sensors, diesel particulate filter (DPF), urea dosing module (UL2), and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be mixed and injected into the system through the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The single module after treatment through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system after treatment module shall be mounted below the frame in the outboard position.

Y__ N__

DIESEL EXHAUST FLUID TANK

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

Y__ N__

ENGINE EXHAUST ACCESSORIES

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

Y__ N__

ENGINE EXHAUST WRAP

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

CLARE FIRE DEPARTMENT

Y__ N__

TRANSMISSION

The drive train shall include an Allison model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters and Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.49:1
2nd	1.86:1
3rd	1.41:1
4th	1.00:1
5th	0.75:1
6th	0.65:1 (if applicable)
Rev	5.03:1

Y__ N__

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will select five (5) speeds of operation. The sixth speed over drive shall be available with the activation of the mode button on the shifting pad.

Y__ N__

TRANSMISSION FEATURE PROGRAMMING

The Allison Gen V-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

<u>Function ID</u>	<u>Description</u>	<u>Wire</u>
<u>assignment</u>		
Inputs		
C	PTO Request	142

CLARE FIRE DEPARTMENT

J	Fire Truck Pump Mode (4th Lockup)	122 / 123
Outputs		
C	Range Indicator	145 (4th)
G	PTO Enable Output	130
	Signal Return	103

Y__ N__

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

Y__ N__

TRANSMISSION SHIFT SELECTOR

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

Y__ N__

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

Y__ N__

TRANSMISSION COOLING SYSTEM

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

Y__ N__

TRANSMISSION DRAIN PLUG

The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.

Y__ N__

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

Y__ N__

PTO LOCATION

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 4:00 o'clock position.

CLARE FIRE DEPARTMENT

DRIVELINE

Y__ N__

All drivelines shall be heavy duty metal tube and equipped with MSI 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat[®]. The drivelines shall include Meritor brand u-joints with thrust washers.

MIDSHIP PUMP / GEARBOX

Y__ N__

A temporary jackshaft driveline shall be installed by the chassis manufacturer to accommodate the mid-ship split shaft pump as specified by the apparatus manufacturer.

MIDSHIP PUMP / GEARBOX MODEL

Y__ N__

The midship pump/gearbox provisions shall be for a Waterous CSUC20 pump.

MIDSHIP PUMP GEARBOX DROP

Y__ N__

The Waterous pump gearbox shall have a "C" (medium length) drop length.

MIDSHIP PUMP RATIO

Y__ N__

The ratio for the midship pump shall be 2.27:1.

MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE

Y__ N__

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 80.00 inches.

PUMP SHIFT CONTROLS

Y__ N__

One (1) air pump shift control panel shall be mounted in the lower left section of the center dash panel. The following shall be provided on the panel: a three (3) position control lever; an engraved PUMP ENGAGED identification light; and an engraved OK TO PUMP identification light. The pump shift control panel shall be black with a yellow border outline and shall include pump instructions. An instruction plate describing the transmission shift selector position used for pumping shall be provided and located so it can be read from the driver's position per NFPA **16.10.1.3**. The road mode shall be selected when the control lever is in the up position and pump mode shall be selected when the control lever is in the down position.

The control lever center position shall exhaust air from both pump and road sides of the pump gear box shift cylinder.

CLARE FIRE DEPARTMENT

PUMP SHIFT CONTROL PLUMBING

Y__ N__

Air connections shall be provided from the air supply tank to the pump shift control valve and from the pump shift control valve to the frame mounted bracket. The frame mounted bracket shall include labeling identifying the pump and road connection points with threaded 0.25 inch NPT fittings on the solenoid for attaching the customer installed pump. The air supply shall be pressure protected from service brake system.

FUEL FILTER/WATER SEPARATOR

Y__ N__

The fuel system shall have a Fleetguard FS20121 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve.

A water in fuel sensor shall be provided and wired to an instrument panel lamp and audible alarm to indicate when water is present in the fuel/water separator.

A secondary fuel filter shall be included as approved by the engine manufacturer.

FUEL LINES

Y__ N__

The fuel system supply and return lines installed from the fuel tank to the engine shall be reinforced nylon tubing rated for diesel fuel. The fuel lines shall be brown in color and connected with brass fittings.

FUEL SHUTOFF VALVE

Y__ N__

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

A second fuel shutoff valve shall be installed in the fuel draw line, near the fuel tank to allow maintenance to be performed with minimal loss of fuel.

ELECTRIC FUEL PRIMER

Y__ N__

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

FUEL TANK

Y__ N__

The fuel tank shall have a capacity of fifty (50) gallons and shall measure 35.00 inches in width X 15.00 inches in height X 24.00 inches in length.

The baffled tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

CLARE FIRE DEPARTMENT

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

Y__ N__

FUEL TANK MATERIAL AND FINISH

The fuel tank shall be constructed of 12 gauge aluminized steel. The exterior of the tank shall be powder coated black and then painted to match the frame components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 Method B, results to be 5B minimum. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794, results to be 5B minimum.

Any proposals offering painted fuel tanks with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

Y__ N__

FUEL TANK STRAP MATERIAL

The fuel tank straps shall be constructed of ASTM A-36 steel. The fuel tank straps shall be powder coated black and then painted to match the frame components if possible.

Y__ N__

FUEL TANK FILL PORT

The fuel tank fill ports shall be offset with the left fill port located in the rearward position and the right fill port located in the middle position on the fuel tank.

Y__ N__

FUEL TANK DRAIN PLUG

A 0.5 inch NPT magnetic drain plug shall be centered in the bottom of the fuel tank.

Y__ N__

FRONT AXLE

The front axle shall include an independent front suspension (IFS) offering superior ride and improved handling.

The suspension shall utilize fully independent double wishbone arms with carrier and kingpin for optimized scrub radius. Air springs are tuned for ride and help reduce suspension weight. The IFS reduces turn radius with improved wheel cut over beam axles. The hydraulic damper shall feature rebound control to ensure the maximum load

CLARE FIRE DEPARTMENT

stability and superior driver comfort. The IFS system shall improve handling and offer better braking because of improved ground to tire ratio. This design shall allow for independent adjustment of the vehicle's alignment settings.

Proposals offering independent front axles comprised of torsion bar style suspensions shall not be considered.

Y__ N__

FRONT AXLE WARRANTY

The front axle shall be warranted by Tuthill for three (3) years or 150,000 miles, which ever comes first. Details of the Tuthill warranty are provided on the PDF document attached to this option.

Y__ N__

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

Y__ N__

FRONT SHOCK ABSORBERS

Two (2) Koni shock absorbers shall be provided and installed as part of the front suspension system. Each shock shall deliver improved road handling and durability.

Y__ N__

FRONT SUSPENSION

The independent front suspension (IFS) system shall improve handling and offer better braking because of improved ground to tire ratio. Lower spring rates and independent wheel travel shall reduce the shock within the wheel and feedback throughout the axle. Increased roll stiffness reduces chassis lean in cornering. The suspension travel of the IFS shall be approximately 6.50 inches, providing 3.00 inches jounce and 3.50 inches rebound of the suspension. This feature shall offer a smoother ride for personnel and sensitive equipment. The IFS front axle shall be rated between 18,000 and 20,000 pounds.

Proposals offering independent front axles comprised of torsion bar style suspensions shall not be considered.

Y__ N__

STEERING COLUMN/ WHEEL

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

CLARE FIRE DEPARTMENT

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

Y__ N__

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

POWER STEERING PUMP

Y__ N__

The hydraulic power steering pump shall be a Vickers V20F and shall be gear driven from the engine. The pump shall be a fixed displacement vane type. The power steering system shall include an oil to air passive cooler.

FRONT AXLE CRAMP ANGLE

Y__ N__

The chassis shall have a front axle cramp angle of 53-degrees to the left and right.

POWER STEERING GEAR

Y__ N__

The power steering gear shall be a TRW model TAS 85/RCS 85.

CHASSIS ALIGNMENT

Y__ N__

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

REAR AXLE

Y__ N__

The rear axle shall be a Meritor model RS-30-185 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 33,000 pounds.

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.56 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

CLARE FIRE DEPARTMENT

REAR AXLE DIFFERENTIAL LUBRICATION

Y__ N__

The rear axle differential shall be lubricated with oil.

REAR AXLE WARRANTY

Y__ N__

The rear axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

REAR WHEEL BEARING LUBRICATION

Y__ N__

The rear axle wheel bearings shall be lubricated with oil.

VEHICLE TOP SPEED

Y__ N__

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

REAR SUSPENSION

Y__ N__

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

TIRE INTERMITTENT SERVICE RATING

Y__ N__

The chassis shall be rated using Intermittent Service ratings provided to the emergency vehicle market by the tire manufacturers as the basis for determining the maximum vehicle load and speed.

FRONT TIRE - NEW CURRENT MODEL YEAR

Y__ N__

The tires shall match the model year of the chassis.

The front tires shall be Goodyear 385/65R-22.5 18PR "J" tubeless radial G296 MSA mixed service tread.

The front tire stamped load capacity shall be 18,740 pounds per axle with a nominal speed rating of 68 miles per hour when properly inflated to 120 pounds per square inch.

The Goodyear Intermittent Service Rating maximum load capacity shall be 20,050 pounds per axle with a speed rating of 68 miles per hour when properly inflated to 120 pounds per square inch.

CLARE FIRE DEPARTMENT

The Goodyear Intermittent Service Rating maximum speed capacity shall be 18,740 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Goodyear Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.

Y__ N__

REAR TIRE - NEW CURRENT MODEL YEAR

The tires shall match the model year of the chassis.

The rear tires shall be Goodyear 315/80R-22.5 20PR "L" tubeless radial G751 MSA mixed service tread.

The rear tire stamped load capacity shall be 33,080 pounds per axle with a nominal speed rating of 68 miles per hour when properly inflated to 130 pounds per square inch.

The Goodyear Intermittent Service Rating maximum load capacity shall match the stamped load rating.

The Goodyear Intermittent Service Rating maximum speed capacity shall be 33,080 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 130 pounds per square inch.

The Goodyear Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.

Y__ N__

REAR AXLE RATIO

The rear axle ratio shall be 5.38:1.

Y__ N__

TIRE PRESSURE INDICATOR

There shall be electronic chrome LED valve caps shipped loose for installation by the OEM which shall illuminate with a red LED when tire pressure drops 8psi provided. The valve caps are self-calibrating and set to the pressure of the tire upon installation.

Y__ N__

FRONT WHEEL

The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch LvL One™ polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and a polished finish that lasts.

CLARE FIRE DEPARTMENT

REAR WHEEL

Y__ N__

The outer rear wheels shall be Alcoa hub piloted, heavy duty, 22.50 inch X 9.00 inch LvL One™ aluminum wheels with a polished outer surface. The inner rear wheels shall be Accuride hub piloted, 22.50 inch X 9.00 inch steel wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

WHEEL PAINT

Y__ N__

The rear steel wheels shall be pretreated in a zinc phosphate bath, coated with a cathode electro deposited white primer base coat (E-Coat). The E-Coat shall exceed 336 hours under industry standard ASTM salt spray testing.

The wheels then shall be powder coated in white all to be completed by the wheel supplier. The powder coat shall exceed 1,200 hours under industry standard ASTM salt spray testing.

WHEEL TRIM

Y__ N__

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons. The baby moons shall have cutouts for oil seal viewing when applicable.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats.

The lug nut covers, baby moons, and high hats shall be RealWheels® brand constructed of 304L grade, non-corrosive stainless steel with a mirror finish. Each wheel trim component shall meet D.O.T. certification.

WHEEL GUARDS

Y__ N__

The rear dual wheels shall include a plastic isolator approximately 0.04" thick installed between the inner and outer wheel to help prevent corrosion caused by metal to metal contact.

BRAKE SYSTEM

Y__ N__

A rapid build-up air brake system shall be provided. The air brakes shall include, at a minimum, a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

CLARE FIRE DEPARTMENT

A four (4) sensor, four (4) modulator Anti-lock Braking System (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A virtual style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

Y__ N__

FRONT BRAKES

The front brakes shall be Bendix ADB 22X disc brakes with 17.00 inch vented rotors.

Y__ N__

REAR BRAKES

The rear brakes shall be Meritor 16.50 inch X 8.63 inch S-cam drum type. The brakes shall feature a cast iron shoe.

Y__ N__

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

Y__ N__

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

CLARE FIRE DEPARTMENT

The parking brake actuation valve shall be mounted on the center of the dash within easy access of the driver and the officer positions.

Y__ N__

REAR BRAKE SLACK ADJUSTERS

Haldex rear brake automatic slack adjusters shall be installed on the axle.

Y__ N__

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral 100 watt heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be located on the right hand frame rail forward of the front wheel behind the right hand cab step.

Y__ N__

FRONT BRAKE CHAMBERS

The front brakes shall be provided with type 24 brake chambers as supplied with the independent front suspension axle.

Y__ N__

REAR BRAKE CHAMBERS

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

Y__ N__

AIR COMPRESSOR

The air compressor provided for the engine shall be a Wabco[®] SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

Y__ N__

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket on the left frame rail behind the battery box.

CLARE FIRE DEPARTMENT

AUXILIARY AIR RESERVOIR

Y__ N__

One (1) auxiliary air reservoir with a 2084 cubic inch capacity shall be installed on the chassis to act as an additional reserve supply to the air system for air horn, air tool, or other non-service brake use. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

MOISTURE EJECTORS

Y__ N__

An automatic moisture ejector with a manual drain provision shall be installed on the wet tank of the air supply system. Manual pet-cock type drain valves shall be installed on all remaining reservoirs of the air supply system.

AIR SUPPLY LINES

Y__ N__

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR TANK SPACERS

Y__ N__

There shall be spacers included with the air tank mounting. The spacers shall move the air tanks 1.50 inches inward towards the center of the chassis. This shall provide clearance between the air tanks and the frame for body U-bolt clearance.

REAR AIR TANK MOUNTING

Y__ N__

If a combination of wheel base, air tank quantity, or other requirements necessitate the location of one or more air tanks to be mounted rear of the fuel tank, these tank(s) will be mounted perpendicular to frame.

WHEELBASE

Y__ N__

The chassis wheelbase shall be determined by manufacturer.

REAR OVERHANG

Y__ N__

The chassis rear overhang shall be determined by manufacturer.

CLARE FIRE DEPARTMENT

Y__ N__

FRAME

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

Y__ N__

FRAME WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY TERMS CAN BE FOUND IN THE CHASSIS WARRANTY DOCUMENT, WHICH CONTAINS THE COMPLETE STATEMENT OF THE WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty period shall commence on the date the vehicle is delivered to the first end user.

CLARE FIRE DEPARTMENT

Y__ N__

REAR TOW DEVICE

The frame rails shall contain (4) holes per frame in a pattern specified by the OEM for mounting tow eyes at the rear of the frame at a location defined by the OEM.

Y__ N__

FRAME PAINT

The frame rails shall be hot dip galvanized prior to assembly and attachment of any components. The components that shall be galvanized shall include:

- Main frame "C" channel or channels

The frame parts which are not galvanized shall be powder coated prior to any attachment of components. Parts which shall be powder coated shall include but are not limited to:

- Steering gear bracket
- Front splayed rails and fish plates
- Bumper extensions
- Cross members
- Cross member gussets
- Fuel tank mounting brackets
- Fuel tank straps (unless material/finish is specified in 3130 subcat)
- Air tanks (unless color coded tanks are specified in 3205 subcat)
- Air tank mounting brackets
- Exhaust mounting brackets
- Air cleaner skid plate
- Radiator skid plate
- Battery supports, battery trays and battery covers

Other non-galvanized under carriage components which are received from the suppliers with coatings already applied shall include but are not limited to:

- Suspension components
- Front and rear axles

All powder coatings, primers and paint used on the non-galvanized components shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-cured pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Y__ N__

FRONT BUMPER

The chassis shall be equipped with a severe duty front bumper constructed from structural steel channel. The bumper material shall be 0.38 thick ASTM A36 steel which shall measure 12.00 inches high with a 3.05 inch flange and shall be 99.00 inches wide with angled front corners.

The bumper shall be primed and painted as specified.

CLARE FIRE DEPARTMENT

FRONT BUMPER EXTENSION LENGTH

Y__ N__

The front bumper shall be extended approximately 21.00 inches ahead of the cab.

FRONT BUMPER PAINT

Y__ N__

The front bumper shall be painted the same as the lower cab color.

FRONT BUMPER TRIM

Y__ N__

The bumper shall include a reflective tape chevron with red and yellow stripes.

FRONT BUMPER APRON

Y__ N__

The 21.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

FRONT BUMPER DISCHARGE

Y__ N__

The chassis shall include frame mounted 2.00 inch diameter plumbed pipe intended for use as a discharge trash line. The discharge pipe shall be routed from the left hand front splay rail area behind the bumper to the area rear of the front axle, ahead of the battery box.

The discharge shall pipe shall be a, 2.00 inch stainless steel schedule 10 tube. The discharge shall include a Victaulic groove for connecting to the pump and discharge hose plumbing on each end of the tube.

The apparatus manufacturer shall plumb the discharge pipe to the pump and shall provide all valves as required.

FRONT BUMPER COMPARTMENT CENTER

Y__ N__

The front bumper shall include a compartment in the bumper apron located in the center between the frame rails which may be used as a hose well. The compartment shall be constructed of 0.13 inch 5052-H32 grade aluminum and shall include drain holes in the bottom corners to allow excess moisture to escape. The compartment shall include a notched cover constructed of 0.19 inch thick bright embossed aluminum tread plate. The notch shall be located in the left front portion of the cover and shall be 4.00 inches in length with a 2.00 inches wide radius.

CLARE FIRE DEPARTMENT

FRONT BUMPER COMPARTMENT COVER HARDWARE

Y__ N__

The front bumper compartment cover(s) shall include gas cylinder stays which shall hold the cover open. Each cover shall be held in the closed position via a D-ring style latch.

MECHANICAL SIREN

Y__ N__

The bumper shall include a cut out which shall accommodate a Federal Q2B™ siren.

MECHANICAL SIREN LOCATION

Y__ N__

The siren shall be recess mounted on the driver side of the front fascia of the bumper, in the outboard position.

AIR HORN

Y__ N__

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

AIR HORN LOCATION

Y__ N__

The air horns shall be recess mounted in the front bumper face, one (1) on the right side of the bumper in the inboard position relative to the right hand frame rail and one (1) on the left side of the bumper in the inboard position relative to the left hand frame rail.

AIR HORN RESERVOIR

Y__ N__

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

ELECTRONIC SIREN SPEAKER

Y__ N__

There shall be one (1) Federal Signal model BP200-EF, 200 watt speaker provided. The speaker shall measure 5.50 inches tall X 7.70 inches wide X 7.80 inches deep. The speaker shall include a Federal Signal "Electric F" style grille which shall measure 6.61 inches tall X 6.78 inches wide.

ELECTRONIC SIREN SPEAKER LOCATION

Y__ N__

The electronic siren speaker shall be located on the front bumper face on the right side outboard of the frame rail in the far outboard position.

CLARE FIRE DEPARTMENT

FRONT BUMPER TOW HOOKS

Y__ N__

Two (2) heavy duty tow hooks, painted to match the frame components, shall be installed in the rearward position out of the approach angle area, bolted directly to the side of each chassis frame rail with grade 8 bolts.

CAB TILT SYSTEM

Y__ N__

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

CAB TILT LIMIT SWITCH

Y__ N__

A cab tilt limit switch shall be installed. The switch will effectively limit the travel of the cab when being tilted. The limit adjustment of the switch shall be preset by the chassis manufacturer to prevent damage to the cab or any bumper mounted option mounted in the cab tilt arc. Further adjustment to the limit by the apparatus manufacturer shall be available to accommodate additional equipment.

CAB TILT CONTROL RECEPTACLE

Y__ N__

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

CLARE FIRE DEPARTMENT

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

Y__ N__

CAB TILT LOCK DOWN INDICATOR

The cab dash shall include a message located within the dual air pressure gauge which shall alert the driver when the cab is unlocked and ajar. The alert message shall cease to be displayed when the cab is in the fully lowered position and the hold down hooks are secured and locked to the cab mounts.

In addition to the alert message an audible alarm shall sound when the cab is unlocked and ajar with the parking brake released.

Y__ N__

CAB WINDSHIELD

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

Y__ N__

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished using electric actuation. The left and right front door windows shall be controlled using a switch on each respective side inner door panel. The driver's door shall include a switch for each powered door window in the cab.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

Y__ N__

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall have a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

Y__ N__

GLASS REAR DOOR RH

The rear right hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

CLARE FIRE DEPARTMENT

GLASS TINT REAR DOOR RIGHT HAND

Y__ N__

The window located in the right hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS REAR DOOR LH

Y__ N__

The rear left hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

GLASS TINT REAR DOOR LEFT HAND

Y__ N__

The window located in the left hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID RH

Y__ N__

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RIGHT HAND

Y__ N__

The window located on the right hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

GLASS SIDE MID LH

Y__ N__

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID LEFT HAND

Y__ N__

The window located on the left hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

CLARE FIRE DEPARTMENT

Y__ N__

CLIMATE CONTROL

A ceiling mounted combination defroster and cabin heating and air conditioning system shall be located above the engine tunnel area. The system covers and plenums shall be of severe duty design made of aluminum which shall be coated with a customer specified interior paint. The design of the system's covers shall provide quick access to washable air intake filters as well as easy access to other serviceable items.

The air delivery plenums provide targeted airflow directly to the vehicle occupants. Six (6) adjustable louvers will provide comfort for the front seat occupants and ten (10) adjustable louvers will provide comfort for the rear crew occupants.

The system shall be capable of producing up to 12 FPM of air velocity at all occupant seating positions. Separate front and rear blower motors shall be of brushless design and shall be controlled independently. It shall be capable of reducing the interior cabin air temperature from 122° F (+/- 3° F) to 80° F in thirty minutes with 50% relative humidity and full solar load as described in SAE J2646.

The system shall also provide heater pull up performance which meets or exceeds the performance requirements of SAE J1612 as well as defrost performance that meets or exceeds the performance requirements of SAE J381.

A gravity drain system shall be provided that is capable of evacuating condensate from the vehicle while on a slope of up to a 13% grade in any direction.

The air conditioning system plumbing shall be a mixture of custom bent zinc coated steel fittings and Aeroquip flexible hose with Aeroquip EZ-Clip fittings.

The overhead heater/defroster plumbing shall include an electronic flow control valve that re-directs hot coolant away from the evaporator, via a bypass loop, as the temperature control is moved toward the cold position.

Any component which needs to be accessed to perform system troubleshooting shall be accessible by one person using basic hand tools. Regularly serviced items shall be replaceable by one person using basic hand tools.

****Spartan Motors Inc. recommends that the overall climate system performance be based off third-party testing in accordance to Society of Automotive Engineering standards as a complete system.**

Individual component level BTU ratings is not an accurate indicator of the performance capability of the completed system. System individual component BTU ratings:

- Air conditioning evaporator total BTU/HR: 82,000
- Air conditioning condenser total BTU/HR: 59,000
- Heater coil total BTU/HR: 98,000

CLARE FIRE DEPARTMENT

Performance data specified is based on testing performed by an independent third-party test facility using a medium four-door 10' Raised roof Gladiator chassis equipped with an ISL engine.

Y__ N__

CLIMATE CONTROL DRAIN

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

Y__ N__

CLIMATE CONTROL ACTIVATION

The heating, defrosting and air conditioning controls shall be in the center dash driver's switch panel, in a position which is easily accessible to the driver. The climate control shall be activated by a rotary switch.

Y__ N__

HVAC OVERHEAD COVER PAINT

The overhead HVAC cover shall be painted with an easy-to-clean gray texture finish.

Y__ N__

A/C CONDENSER LOCATION

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

Y__ N__

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted compressor. The compressor shall be compatible with R134-a refrigerant.

****Spartan Motors Inc. recommends that the overall climate system performance be based off third-party testing in accordance to Society of Automotive Engineering standards as a complete system.**

Individual component level ratings are not an accurate indicator of the performance capability of the completed system.

Refrigerant Compressor displacement: 19.1 cubic inches per revolution.

Y__ N__

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

CLARE FIRE DEPARTMENT

The engine tunnel insulation shall measure approximately 0.30 inch thick including a multi-layer foil faced glass cloth and polyester fiber layer. The foil surface acts as protection against heat, moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by acrylic pressure sensitive adhesive.

Y__ N__

INTERIOR TRIM FLOOR

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

Y__ N__

INTERIOR TRIM

The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

Y__ N__

REAR WALL INTERIOR TRIM

The rear wall of the cab shall be trimmed with vinyl.

Y__ N__

HEADER TRIM

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

Y__ N__

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation. The center dash electrical access cover shall include a gas cylinder stay which shall hold the cover open during maintenance.

Y__ N__

TRIM LH DASH

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

CLARE FIRE DEPARTMENT

TRIM RH DASH

Y__ N__

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

ENGINE TUNNEL TRIM

Y__ N__

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

POWER POINT DASH MOUNT

Y__ N__

The cab shall include a 12 volt cigarette lighter type receptacle in the cab dash to provide a power source for 12 volt electrical equipment. The cab shall also include one (1) dual universal serial bus (USB) charging receptacle in the cab dash switch panel to provide a power source for USB chargeable electrical equipment. Each dual USB receptacle shall include two ports and shall be capable of up to a 5 Volt 2.1 amp output. Port 1 is optimized for fast charging at 1 amp. Port 2 is optimized for fast charging up to 2.1 amps, when used individually. The receptacles shall be wired battery direct.

AUXILIARY POWER POINT ENGINE TUNNEL

Y__ N__

The cab interior shall include two (2) 12 volt cigarette lighter type receptacles to provide power sources for 12 volt electrical equipment. The receptacles shall be connected directly to the batteries. The receptacles shall be located on the rear of the engine tunnel near the top, one (1) near the left corner and one (1) near the right corner.

STEP TRIM

Y__ N__

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of SAE 304 stainless steel with embossed perforations and diamond shaped cutout. The perforations and cutouts shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The step shall feature a splash guard to reduce water and debris from splashing in to the step. The splash guard shall have drainage holes beneath the back of the step to allow debris and water to flow through rather than becoming trapped within the stepping surface. The stainless steel material shall have a number 8 mirror finish. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed with a Flex-Tred[®] adhesive grit surface material.

CLARE FIRE DEPARTMENT

UNDER CAB ACCESS DOOR

Y__ N__

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

INTERIOR DOOR TRIM

Y__ N__

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

DOOR TRIM CUSTOMER NAMEPLATE

Y__ N__

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

CAB DOOR TRIM REFLECTIVE

Y__ N__

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes and a Spartan logo. The chevron tape shall measure 6.00 inches in height.

INTERIOR GRAB HANDLE "A" PILLAR

Y__ N__

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Y__ N__

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

Y__ N__

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

CLARE FIRE DEPARTMENT

INTERIOR SOFT TRIM COLOR

Y__ N__

The cab interior soft trim surfaces shall be gray in color.

INTERIOR TRIM SUNVISOR

Y__ N__

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

INTERIOR FLOOR MAT COLOR

Y__ N__

The cab interior floor mat shall be gray in color.

CAB PAINT INTERIOR DOOR TRIM

Y__ N__

The inner door panel surfaces shall be painted with an easy clean-to-clean gray texture finish.

HEADER TRIM INTERIOR PAINT

Y__ N__

The metal surfaces in the header area shall be coated with an easy-to-clean gray texture finish.

TRIM CENTER DASH INTERIOR PAINT

Y__ N__

The entire center dash shall be coated with an easy-to-clean matte gray texture finish. Any accessory pods attached to the dash shall also be painted this color.

TRIM LH DASH INTERIOR PAINT

Y__ N__

The left hand dash shall be painted with an easy-to-clean matte gray texture finish.

TRIM RIGHT HAND DASH INTERIOR PAINT

Y__ N__

The right hand dash shall be painted with an easy-to-clean matte gray texture finish.

DASH PANEL GROUP

Y__ N__

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

CLARE FIRE DEPARTMENT

SWITCHES CENTER PANEL

Y__ N__

The center dash panel shall include six (6) switch positions in the upper left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

Y__ N__

The left dash panel shall include one (1) windshield wiper/washer control switch located in the left hand side of the panel. The switch shall have backlighting provided.

SWITCHES RIGHT PANEL

Y__ N__

The right dash panel shall include no rocker switches or legends.

SEAT BELT WARNING

Y__ N__

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall provide a visual warning indicator in the Vista display and control screen(s), an indicator light in the instrument panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

SEAT MATERIAL

Y__ N__

The Bostrom Firefighter seats shall include a covering of extra high strength, wear resistant fabric made of durable low seam Durawear Plus™ ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Durawear Plus™ meets or exceeds specification of the common trade name Imperial 1800. The material meets FMVSS 302 flammability requirements.

If applicable, Theatre style seats located in the cab shall be high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

Y__ N__

CLARE FIRE DEPARTMENT

SEAT COLOR

All seats supplied with the chassis shall be gray in color. All seats shall include red seat belts.

Y__ N__

SEAT BACK LOGO

The seat back shall include the "Spartan" logo. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

Y__ N__

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom 500 Series Firefighter Sierra model seat. The seat shall feature eight-way electric positioning. The eight positions shall include up and down, fore and aft with 8.00 inches of travel, back angle adjustment and seat rake adjustment. The seat shall feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches measured with the seat height adjusted to the lowest position of travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

Y__ N__

SEAT BACK DRIVER

The driver's seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured head rest.

Y__ N__

SEAT MOUNTING DRIVER

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

CLARE FIRE DEPARTMENT

Y__ N__

OCCUPANT PROTECTION DRIVER

The driver's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The driver's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the driver, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the driver's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the driver in a qualifying event by covering the window and the upper portion of the door.
- Dual knee airbags (patent pending) with energy management mounting (patent pending) - protects the driver's lower body from dangerous surface contact injuries, acceleration injuries, and from intrusion as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

Steering wheel airbag - protects the driver's head, neck, and upper torso from contact injuries, acceleration injuries, and contact points with intrusive surfaces as a result of a collision.

Y__ N__

SEAT OFFICER

The officer's seat shall be a H.O. Bostrom 500 Series Sierra seat model. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model

CLARE FIRE DEPARTMENT

of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

Y__ N__

SEAT BACK OFFICER

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto- locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

Y__ N__

SEAT MOUNTING OFFICER

The officer's seat shall offer a special mounting position which is 2.00 inches rearward of the standard location offering increased leg room for the occupant.

Y__ N__

OCCUPANT PROTECTION OFFICER

The officer's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The officer's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the officer, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the officer's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a

CLARE FIRE DEPARTMENT

result of a collision as well as provides ejection mitigation protection to the officer in a qualifying event by covering the window and the upper portion of the door.

Knee airbags - protects the officer's lower body from dangerous surface contact injuries, acceleration injuries, and from contact points with intrusive surfaces as a result of a collision as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

Y__ N__

POWER SEAT WIRING

The power seat or seats installed in the cab shall be wired directly to battery power.

Y__ N__

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

Y__ N__

SEAT REAR FACING OUTER LOCATION

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

Y__ N__

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

CLARE FIRE DEPARTMENT

Y__ N__

SEAT BACK REAR FACING OUTER

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

Y__ N__

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

Y__ N__

OCCUPANT PROTECTION RFO

The rear facing outer seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each rear facing outer seating position APS shall include:

- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - protects each occupant's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to each occupant in a qualifying

CLARE FIRE DEPARTMENT

event by covering the windows and walls adjacent to each seating position with an airbag custom designed for each cab configuration.

Y__ N__

SEAT FORWARD FACING CENTER LOCATION

The crew area shall include two (2) forward facing center crew seats with both located at the center of the rear wall.

Y__ N__

SEAT CREW FORWARD FACING CENTER

The forward facing center seat shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position. The seat and cushion shall be hinged and compact in design for additional room. The seat shall include a "Fold and Hold" feature so that the cushion shall remain in the seated position and simply touched to flip up.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

Y__ N__

SEAT BACK FORWARD FACING CENTER

The forward facing center seat shall feature a SecureAll™ self contained breathing apparatus (SCBA) locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

CLARE FIRE DEPARTMENT

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

Y__ N__

OCCUPANT PROTECTION FFC

The forward facing center seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each forward facing center seating position APS shall include:

- APS advanced seatbelt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to crew seating with an airbag custom designed for each cab configuration.

Y__ N__

SEAT FRAME FORWARD FACING

The forward facing center seating positions shall include an enclosed seat frame located and installed on the rear wall. The seat frame shall measure 42.38 inches wide X 12.38 inches high X 22.00 inches deep. The seat frame shall be constructed of Marine Grade 5052-H32 0.19 inch thick aluminum plate. The seat box shall be painted with the same color as the remaining interior.

Y__ N__

SEAT FRAME FORWARD FACING STORAGE ACCESS

There shall be two (2) access points to the seat frame storage area, one (1) on each side of the seat frame. Each access point shall be covered by a hinged door which measures 15.00 inches in width X 10.63 inches in height.

Y__ N__

SEAT MOUNTING FORWARD FACING CENTER

The forward facing center seats shall be installed facing the front of the cab.

CLARE FIRE DEPARTMENT

CAB FRONT UNDERSEAT STORAGE ACCESS

Y__ N__

The left and right under seat storage areas shall have a solid aluminum hinged door with non-locking latch.

SEAT COMPARTMENT DOOR FINISH

Y__ N__

All underseat storage compartment access doors shall have an easy-to-clean gray texture finish.

WINDSHIELD WIPER SYSTEM

Y__ N__

The cab shall include a triple arm linkage wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers; each shall be affixed to a radial arm. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

Y__ N__

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

CAB DOOR HARDWARE

Y__ N__

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of a fiber reinforced plastic composite with a black matt finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

DOOR LOCKS

Y__ N__

Each cab entry door shall include a manually operated door lock. Each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.

CLARE FIRE DEPARTMENT

GRAB HANDLES

Y__ N__

The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The grab handle shall be made of SAE 304 stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.

REARVIEW MIRRORS

Y__ N__

Retrac Aerodynamic West Coast style dual vision mirror heads model 613305 shall be provided and installed on each of the front cab doors.

The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.

The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an integral convex mirrors installed in the mirror head below the flat glass to provide a wider field of vision. The flat and convex mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The flat and convex mirrors shall be heated for defrosting in severe cold weather conditions.

The mirrors shall be constructed of a vacuum formed chrome plated ABS plastic housing that is corrosion resistant and shall include the finest quality non-glare glass.

REARVIEW MIRROR HEAT SWITCH

Y__ N__

The heat for the rearview mirrors shall be controlled through a virtual button on the Vista display and control screen.

CAB FENDER

Y__ N__

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 5.00 inches wide made of polished aluminum.

MUD FLAPS FRONT

Y__ N__

The front wheel wells shall have mud flaps installed on them.

CAB EXTERIOR FRONT & SIDE EMBLEMS

Y__ N__

The cab shall include three (3) Spartan emblems. There shall be one (1) installed on the front air intake grille and one (1) emblem on each of the cab sides. The cab shall also include one (1) Advanced Protection System shield emblem on each front door.

CLARE FIRE DEPARTMENT

Y__ N__

IGNITION

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

Y__ N__

BATTERY

The single start electrical system shall include six (6) Harris BCI 31 925 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

Y__ N__

BATTERY TRAY

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

Y__ N__

BATTERY BOX COVER

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall be coated the same as the battery box and shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

Y__ N__

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

Y__ N__

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step, 8.00 inches apart. The studs shall

CLARE FIRE DEPARTMENT

allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

Y__ N__

ALTERNATOR

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

Y__ N__

STARTER MOTOR

The single start electrical system shall include a Delco brand starter motor.

Y__ N__

BATTERY CONDITIONER

A Kussmaul Auto Charge 40 LPC battery conditioner shall be supplied. The battery conditioner shall provide a 40 amp output for the chassis batteries and a 15 amp output circuit for accessory loads. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

Y__ N__

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

Y__ N__

AUXILIARY AIR COMPRESSOR

A Kussmaul Auto Pump 120V air compressor shall be supplied. The air compressor shall be installed under the dashboard on the right-hand side, forward of the officer's seating position. The air compressor shall be plumbed to the air brake system to maintain air pressure.

Y__ N__

ELECTRICAL INLET LOCATION

An electrical inlet shall be installed on the left hand side of cab over the wheel well.

Y__ N__

ELECTRICAL INLET

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

Amp Draw Reference List:

Kussmaul 40 LPC Charger - 5 Amps

Kussmaul 40/20 Charger - 8.5 Amps

CLARE FIRE DEPARTMENT

Kussmaul 80 LPC Charger - 13 Amps
Kussmaul EV-40 - 6.2 Amps
Blue Sea P12 7532 - 7.5 Amps
Iota DLS-45/IQ4 - 11 Amps
1000W Engine Heater - 8.33 Amps
1500W Engine Heater - 12.5 Amps
120V Air Compressor - 4.2 Amps

Y__ N__

ELECTRICAL INLET CONNECTION

The electrical inlet shall be connected to the battery conditioner and the air pump.

Y__ N__

ELECTRICAL INLET COLOR

The electrical inlet connection shall include a yellow cover.

Y__ N__

HEADLIGHTS

The cab front shall include two (2) FireTech rectangular LED headlamps with high/low beam in the same housing and two (2) separate FireTech LED high beam only headlamps mounted in bright chrome bezels.

Y__ N__

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

Y__ N__

FRONT TURN SIGNALS

The front fascia shall include two (2) Whelen model M6 4.00 inch X 6.00 inch amber LED turn signals which shall be installed in a chrome radius mount housing above and outboard of the front warning and head lamps.

Y__ N__

SIDE TURN/MARKER LIGHTS

The sides of the cab shall include two (2) Tecniq S170 LED side marker lights which shall be provided just behind the front cab radius corners. The lights shall be amber with chrome bezels.

Y__ N__

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) marker lamps on the front of the vehicle designating identification and clearance. There shall be five (5) face mounted lights integrated into the scene light.

CLARE FIRE DEPARTMENT

HEADLIGHT AND MARKER LIGHT ACTIVATION

Y__ N__

The headlights and marker lights shall be controlled via a virtual button on the Vista display. There shall be a virtual dimmer control on the Vista display to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the ignition switch is in the "On" position and the parking brake is released.

GROUND LIGHTS

Y__ N__

The ground lighting shall be activated when the parking brake is set, by the opening of the door on the respective cab side, and through a virtual button on the Vista display and control screen.

GROUND LIGHTS

Y__ N__

Each door shall include a Tecniq T44 LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

LOWER CAB STEP LIGHTS

Y__ N__

The middle step located at each door shall include a Tecniq T44 LED light which shall activate with the opening of the respective door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

INTERMEDIATE STEP LIGHTS

Y__ N__

The intermediate step well area at each door shall include a TecNiq D06 LED light within a chrome housing. The Egress step lights shall provide visibility to the step well area for the first step exiting the vehicle. The Egress step lights shall activate with Entry step lighting.

LIGHTBAR PROVISION

Y__ N__

There shall be one (1) light bar installed on the cab roof. The light bar shall be provided and installed by Spartan Chassis. The light bar installation shall include a lowered mounting that shall place the light bar just above the junction box and wiring to a control switch on the cab dash.

CAB FRONT LIGHTBAR MODEL

Y__ N__

The cab shall be provided with one (1) Whelen model F4N72 light bar. The light bar shall be 72.00 inches in length and feature eighteen (18) customizable pods.

The lightbar shall feature eight (8) red and two (2) white LED modules.

CLARE FIRE DEPARTMENT

LIGHTBAR SWITCH

Y__ N__

The light bar shall be controlled through a virtual button on the Vista display and control screen. There shall be an additional button located on the Vista display and control screen to control the clear lights.

FRONT SCENE LIGHTS

Y__ N__

The front of the cab shall include one (1) Fire Research Crestline CLA1000-A68 LED scene light installed on the brow of the cab. The light shall feature (5) five integrated marker lights with low beam and narrow flood optics. The light shall generate 17,800 lumens of light.

The housing and brackets shall be powder coated white.

FRONT SCENE LIGHT LOCATION

Y__ N__

There shall be one (1) scene light mounted center on the front brow of the cab.

FRONT SCENE LIGHTS ACTIVATION

Y__ N__

The front scene lighting shall be activated by two (2) virtual buttons on the Vista display and control screen(s) one (1) for low beam lights and one switch (1) for the narrow flood light.

SIDE SCENE LIGHTS

Y__ N__

The cab shall include two (2) Whelen Pioneer model PCPSM1C LED surface mount lights installed one (1) on each side of the cab.

The PCPSM1C configuration shall consist of twelve (12) white Super-LEDs for the spot light with a specialized spot reflector on the bottom, twenty-four (24) white Super-LEDs in the flood light with a clear optic collimator/metalized reflector assembly on the top, and a clear non-optic polycarbonate lens. Each lamp head shall draw 6.0 amps and generate 7,800 lumens. Each lamp head shall measure 6.37 inches in height X 8.97 inches in width. Each lamp head housing shall be chrome plated.

SIDE SCENE LIGHT LOCATION

Y__ N__

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab "B" pillar in the 10.00 inch raised roof portion of the cab between the front and rear crew doors.

CLARE FIRE DEPARTMENT

SIDE SCENE ACTIVATION

Y__ N__

The scene lights shall be activated by two (2) virtual buttons on the Vista display and control screen(s), one (1) for each light.

INTERIOR OVERHEAD LIGHTS

Y__ N__

The cab shall include a two-section, red and clear Weldon LED dome lamp located over each door. The dome lamps shall be rectangular in shape and shall measure approximately 7.00 inches in length X 3.00 inches in width with a black colored bezel. The clear portion of each lamp shall be activated by opening the respective door and via the multiplex display and both the red and clear portion can be activated by individual push lenses on each lamp.

An additional incandescent three (3) light module with dual map lights shall be located over the engine tunnel which can be activated by individual switches on the lamp.

ENGINE COMPARTMENT LIGHT

Y__ N__

There shall be a LED NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

DO NOT MOVE APPARATUS LIGHT

Y__ N__

The front headliner of the cab shall include a flashing red TecNiq K50 LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed, or an apparatus compartment door is not closed, and the parking brake is released.

MASTER WARNING SWITCH

Y__ N__

A master switch shall be included, as a virtual button on the Vista display and control screen which shall be labeled "E Master" for identification. The button shall feature control over all devices wired through it. Any warning device switches left in the "ON" position when the master switch is activated shall automatically power up.

HEADLIGHT FLASHER

Y__ N__

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

CLARE FIRE DEPARTMENT

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

Y__ N__

HEADLIGHT FLASHER SWITCH

The flashing headlights shall be activated through a virtual button on the Vista display and control screen.

Y__ N__

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen M6 Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel

Y__ N__

INBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the inboard positions shall be red.

Y__ N__

OUTBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen M6 Super LED front warning lights in the left and right outboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

Y__ N__

OUTBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the outboard position shall be red.

Y__ N__

FRONT WARNING SWITCH

The front warning lights shall be controlled through a virtual control on the Vista display and control screen. This switch shall be clearly labeled for identification.

Y__ N__

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen M6 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn.

Y__ N__

INTERSECTION WARNING LIGHTS COLOR

The intersection lights shall be red.

CLARE FIRE DEPARTMENT

INTERSECTION WARNING LIGHTS LOCATION

Y__ N__

The intersection lights shall be mounted centered front to rear on the flat portion of the side of the bumper tail.

SIDE WARNING LIGHTS

Y__ N__

The cab sides shall include two (2) Whelen M6 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

SIDE WARNING LIGHTS COLOR

Y__ N__

The warning lights located on the side of the cab shall be red.

SIDE WARNING LIGHTS LOCATION

Y__ N__

The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

SIDE AND INTERSECTION WARNING SWITCH

Y__ N__

The side warning lights shall be controlled through a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

TANK LEVEL LIGHTS

Y__ N__

There shall be two (2) FRC MaxVision surface mount water level light strips.

The light strips shall feature four (4) colors of LED lights to indicate the fluid level of a tank. The colors from top to bottom shall be green, blue, amber, and red.

TANK LEVEL LIGHTS ACTIVATION

Y__ N__

The tank level lights shall be pre-wired and coiled at rear of the cab for connection to the apparatus by the body builder.

TANK LEVEL LIGHTS LOCATION

Y__ N__

There shall be water level lights mounted on each side of the cab, centered between the rear cab doors and the rear corners of the cab.

CLARE FIRE DEPARTMENT

SIREN CONTROL HEAD

Y__ N__

A Federal PA4000 electronic siren control head shall be provided and flush mounted in the switch panel with a location specific to the customer's needs. The siren shall feature 200-watt output, wail, radio broadcast, public address, yelp, priority tones and a noise cancelling microphone.

STEERING WHEEL HORN BUTTON SELECTOR SWITCH

Y__ N__

A virtual button on the Vista display and control screen shall be provided to allow control of either the electric horn or the air horn from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position to meet FMCSA requirements.

AUDIBLE WARNING RH FOOT SWITCH

Y__ N__

A foot switch wired to actuate the air horn(s) shall be mounted in the front section of the cab for use by the officer.

AIR HORN FOOT SWITCH RH

Y__ N__

The air horn foot switch shall be a Linemaster model 491-S.

AIR HORN FOOT SWITCH RH LOCATION

Y__ N__

The air horn foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.

AIR HORN AUXILIARY ACTIVATION

Y__ N__

The air horn activation shall be accomplished by a black momentary push button on the switch panel. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

AIR HORN CIRCUIT INTERLOCK

Y__ N__

The air horn shall only be active when master warning switch is on to prevent accidental engagement.

BACK-UP ALARM

Y__ N__

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.

CLARE FIRE DEPARTMENT

Y__N__

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

A twenty eight (28) icon lightbar message center with integral LCD odometer/trip odometer shall be included. The odometer shall display up to 999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD message center screen shall be capable of custom configuration by the users for displaying certain vehicle status and diagnostic functions.

The instrument panel shall contain the following gauges:

One (1) three-movement gauge displaying vehicle speed, fuel level, and Diesel Exhaust Fluid (DEF) level. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H. The scale on the fuel and DEF level gauges shall read from empty to full as a fraction of full tank capacity. Red indicator lights in the gauge and an audible alarm shall indicate low fuel or low DEF at 1/8th tank level.

One (1) three-movement gauge displaying engine RPM, and primary and secondary air system pressures shall be included. The scale on the tachometer shall read from 0 to 3000 RPM. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI) with a red line zone indicating critical levels of air pressure. Red indicator lights in the gauge and an audible alarm shall indicate low air pressure.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, voltmeter, and transmission temperature shall be included. The scale on the engine oil pressure gauge shall read from 0 to 100 pounds PSI with a red line zone indicating critical levels of oil pressure. A red indicator light in the gauge and audible alarm shall indicate low engine oil pressure. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (°F) with a red line zone indicating critical coolant temperatures. A red indicator light in the gauge and audible alarm shall indicate high coolant temperature. The scale on the voltmeter shall read from 9 to 18 volts with a red line zone indicating critical levels of battery voltage. A red indicator light in the gauge and an audible alarm shall indicate high or low system voltage. The low voltage alarm shall indicate when the system voltage has dropped below 11.8 volts for more than 120 seconds in accordance with the requirements of NFPA 1901. The scale on the transmission temperature gauge shall read from 100 to 300 degrees °F with a red line zone indicating critical temperatures. A red indicator light in the gauge and an audible alarm shall indicate a high transmission temperature.

The light bar portion of the message center shall include twenty-eight (28) LED backlit indicators. The lightbar shall be split with fourteen (14) indicators on each side of the LCD message screen. The lightbar shall contain the following indicators and produce the following audible alarms when supplied in conjunction with applicable configurations:

CLARE FIRE DEPARTMENT

RED INDICATORS

Stop Engine - indicates critical engine fault
Air Filter Restricted - indicates excessive engine air intake restriction
Park Brake - indicates parking brake is set
Seat Belt - indicates a seat is occupied and corresponding seat belt remains unfastened
Low Coolant - indicates critically low engine coolant
Cab Tilt Lock - indicates the cab tilt system locks are not engaged.

AMBER INDICATORS

Malfunction Indicator Lamp (MIL) - indicates an engine emission control system fault
Check Engine - indicates engine fault
Check Transmission - indicates transmission fault
Anti-Lock Brake System (ABS) - indicates anti-lock brake system fault
High exhaust system temperature – indicates elevated exhaust temperatures
Water in Fuel - indicates presence of water in fuel filter
Wait to Start - indicates active engine air preheat cycle
Windshield Washer Fluid – indicates washer fluid is low
DPF restriction - indicates a restriction of the diesel particulate filter
Regen Inhibit - indicates regeneration of the DPF has been inhibited by the operator
Range Inhibit - indicates a transmission operation is prevented and requested shift request may not occur.
SRS - indicates a problem in the supplemental restraint system
Check Message - indicates a vehicle status or diagnostic message on the LCD display requiring attention.

GREEN INDICATORS

Left and Right turn signal indicators
ATC - indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system
High Idle - indicates engine high idle is active.
Cruise Control - indicates cruise control is enabled
OK to Pump - indicates the pump is engaged and conditions have been met for pump operations
Pump Engaged - indicates the pump transmission is currently in pump gear
Auxiliary Brake - indicates secondary braking device is active

BLUE INDICATORS

High Beam indicator

AUDIBLE ALARMS

Air Filter Restriction
Cab Tilt Lock
Check Engine
Check Transmission
Open Door/Compartment
High Coolant Temperature
High or Low System Voltage
High Transmission Temperature
Low Air Pressure
Low Coolant Level
Low DEF Level
Low Engine Oil Pressure
Low Fuel
Seatbelt Indicator

CLARE FIRE DEPARTMENT

Stop Engine
Water in Fuel
Extended Left/Right Turn Signal On
ABS System Fault

Y__ N__

BACKLIGHTING COLOR

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

Y__ N__

CAMERA REAR

One (1) Audiovox Voyager heavy duty box shaped HD camera shall be shipped loose for OEM installation in the body to afford the driver a clear view to the rear of the vehicle.

The camera system shall include a one-way communication device that shall be an integral part of the rear camera for the use of voice commands directly to the driver. The rear camera display shall activate when the vehicle's transmission is placed in reverse.

Y__ N__

CAMERA DISPLAY

The camera system shall be wired to a single Weldon Vista display located on the driver's side dash. The camera system display can be activated through the Vista display panel.

Y__ N__

CAMERA SPEAKER

The rear camera shall be wired to speaker(s) in the cab and shall audible to the driver and officer. There shall be a virtual button provided on the Vista display and control panel to deactivate the speaker(s).

Y__ N__

COMMUNICATION ANTENNA

An antenna base, for use with an NMO type antenna, shall be mounted on the left hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by Spartan Chassis. The antenna base shall be an Antenex model MABVT8 made for either a 0.38 inch or 0.75 inch receiving hole in the antenna and shall include 17 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna base design provides the most corrosion resistance and best power transfer available from a high temper all brass construction and gold plated contact design. The antenna base shall be provided by Spartan.

Y__ N__

COMMUNICATION ANTENNA CABLE ROUTING

The antenna cable shall be routed from the antenna base mounted on the roof to the area inside the center rocker switch console.

CLARE FIRE DEPARTMENT

Y__ N__

AUXILIARY COMMUNICATION ANTENNA

An auxiliary antenna base, for use with and NMO type antenna, shall be installed on the cab. The antenna base shall be an Antenex model MABVT8 and shall include 17.00 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna shall be mounted on the right hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by Spartan Chassis. The antenna base shall be provided by Spartan.

Y__ N__

AUXILIARY COMMUNICATION ANTENNA CABLE ROUTING

The auxiliary antenna cable shall be routed from the antenna base mounted on the roof to the area inside the center rocker switch console.

Y__ N__

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

Y__ N__

FIRE EXTINGUISHER

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

Y__ N__

DOOR KEYS

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

Y__ N__

DIAGNOSTIC SOFTWARE OCCUPANT PROTECTION

Diagnostic software for the Spartan Advanced Protection System shall be available for free download from the Spartan Chassis website to Spartan authorized OEMs, dealers and service centers, as well as the vehicle owner.

The software has been validated to be compatible with the following RP1210 interface adapters:

- Dearborn Group DPA4 Plus
- Noregon Systems JPRO[®] DLA+
- Cummins INLINE5
- Cummins INLINE6
- NexIQ[™] USB-Link[™]

The software and adapter utilize the SAE J1939-13 heavy duty nine (9) pin connector which is located below the driver's side dash to the left of the steering column.

CLARE FIRE DEPARTMENT

Y__ N__

WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN FIRE CHASSIS LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twenty-four (24) months, or the first 36,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

Y__ N__

CHASSIS OPERATION MANUAL

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

Y__ N__

ENGINE AND TRANSMISSION OPERATION MANUALS

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

(1) Hard copy of the Engine Operation and Maintenance manual with digital copy

(1) Digital copy of the Transmission Operator's manual

(1) Digital copy of the Engine Owner's manual

Y__ N__

CAB/CHASSIS AS BUILT WIRING DIAGRAMS

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

Y__ N__

DRIVELINE LAYOUT CONFIRMATION

During the design phase of the chassis the Chassis driveline engineer shall submit the driveline layout to an OEM engineer to review the chassis design for any potential problems integrating the OEM body to the chassis. The OEM engineer shall provide approval to the driveline engineer prior to driveline bills of materials being released.

CLARE FIRE DEPARTMENT

Y__N__

EXHAUST MODIFICATION

The chassis exhaust pipe and muffler shall be extended to the front of the right rear wheel and shall be pointed out. Any heat shields required to protect body and/or compartments from heat shall be installed.

Y__N__

CHASSIS SETUP

The chassis shall have adjustments made to insure the proper configuration for accepting pumps and/or bodies. This shall include the repositioning air tanks, frame cross members and miscellaneous adjustments.

Y__N__

REAR TOW EYES

There shall be two (2) rear tow eyes below the body that will be attached to the rear of the chassis frame. The tow eyes shall be extended toward the rear of the apparatus body.

Y__N__

PUMP OPERATOR'S PANEL - SIDE MOUNT

The operator's control panel shall be located on the left side of the apparatus. The upper portion of the panel will include the engine function and auxiliary gauges, gauge test panel, pump governor, discharge gauges for secondary discharge lines. It will be hinged to swing open, held at the end with appropriate fasteners.

The center portion of the panel will serve as a structural member and a guide for auxiliary discharge line controls.

The lower portion of the left panel will include all side discharge ports, gauges and drains, pony suction and main suction inlets, primer control and tank to pump lines.

The upper portion of the right pump panel will be a hinged door with an appropriate latch mechanism. This will allow for easy service access to the pump, primer oil reservoir and plumbing.

The lower portion of the right panel will include the right discharges, pony suction (if applicable) and the main suction inlet for the pump.

The valve control levers shall be of the horizontally operated locking type. Each lever shall have a chrome T-handle. The valve control levers shall be located directly adjacent to one another and mounted in line as to be in the same position when shut off. Each valve control lever shall be connected directly to it's respective valve by a rod to form a "direct linkage" control system. The specified pressure gauges shall be located adjacent to their respective discharge control levers. Each control shall be clearly marked by **color-coded** name plates permanently affixed to the operator's panel.

CLARE FIRE DEPARTMENT

PUMP PANEL LAYOUT

All discharge valves, 1-1/2" and larger controlled at the operator's control panel shall have corresponding pressure gauges. Gauges shall be 2-1/2" in diameter, 0-400 PSI graduated, silicone filled.

The apparatus body and pump panel modules shall be constructed as independent structures to allow body flexing and to prevent fatigue from normal chassis movement. There shall be a 1" wide gasket installed between the body and the pump panel module.

The front of the pump module shall be enclosed with aluminum diamond plate.

Y__N__

PUMP PANELS AND DOORS

The pump panels and pump access doors shall be constructed of brushed stainless steel.

Y__N__

FLIP-DOWN PUMP PANEL PLATFORMS

Two (2) diamondplate aluminum steps will be installed on the outer edges of the pump panel area, one (1) each side. The step will be full width and approximately 7" deep.

Y__N__

SIDE MOUNT FIRE PUMP MODULE INSTALLATION

The fire pump, pump assembly, plumbing, intakes, outlets, and accessories shall be installed on the chassis.

Y__N__

LEFT PUMP PANEL LIGHT

The left pump panel shall be lit with LED strip lighting. Each strip light shall be mounted under a formed light shield. The lights will be controlled by the parking brake switch.

Y__N__

RIGHT PUMP PANEL LIGHT

The right pump panel shall be lit with LED strip lighting. Each strip light shall be mounted under a formed light shield. The lights will be controlled by the parking brake switch.

Y__N__

COLOR CODED PUMP PANEL

All valve controls, discharges and drains shall be labeled and color coded to the customer's specifications.

CLARE FIRE DEPARTMENT

Y__N__

RUNNINGBOARD COMPARTMENTS (2)

Two (2) compartments will be provided in the runningboards below the suction inlets, one (1) each side. The compartments will be constructed from aluminum plate.

Drains and Dri-Deck material will be provided in the bottom of each compartment.

A restraint device shall be installed for the hose.

Y__N__

SINGLE STAGE FIRE PUMP

A Waterous Model CSUC20 fire pump shall be midship mounted, single stage centrifugal type. In addition to meeting NFPA 1901 requirements, it shall be constructed and mounted in accordance with the following specifications.

Fire pump shall incorporate high strength involute tooth form Morse HV chain drive transmission. Benefits of the chain drive include quiet, noiseless operation at high shaft speeds, and improved power-transmitting capabilities due to the fact that the chain wraps itself halfway around the gear distributing a very uniform pattern of tooth engagement. Pump transmissions utilizing spur or helical drive gears that create high noise levels at elevated speeds and only permit minimal tooth to tooth engagement are not acceptable.

The shift engagement shall be accomplished by a free sliding collar and shall incorporate an internal locking mechanism to insure that collar will be maintained in ROAD or PUMP operation.

Suction intake arms shall be provided with removable die cast zinc screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.

At time of delivery the pump shall be tested and rated as follows:

- 100% of rated capacity at 150 pounds net pressure
- 70% of rated capacity at 200 pounds net pressure
- 50% of rated capacity at 250 pounds net pressure
- 100% of rated capacity at 165 pounds net pressure

Impeller hubs shall be "Flame Plated", impregnated with tungsten carbide to assure maximum pump life and efficiency despite the presence of abrasive particles, such as fine sand, in the water being pumped.

The impeller shaft shall be of a "separable" design to allow true separation of the transmission from the pump without disassembly or disturbing either component. Fire pumps requiring disassembly of pump body and transmission to service either component are not acceptable.

The main pump body shall be horizontally split and shall be in two sections for easy removal of the entire impeller assembly including wear rings, without disturbing setting of the pump on the chassis. Pump case halves shall be bolted together on a single horizontal plane using a single gasket.

The pump body is to be of close grain gray iron with all moving parts which come into contact with water to be of bronze or stainless steel.

CLARE FIRE DEPARTMENT

The pump must be tested by the pump manufacturer for 10 minutes hydrostatically at a pressure of 500 PSIG. Certification by the pump manufacturer must be provided.

The pump shall be provided with a plate giving the rated flow at "capacity" and "pressure" test pressures, together with the R.P.M. of the engine at those pressures and deliveries and mounted in clear view of the pump operators panel. Data plate shall include model and serial numbers of the pump body and chain transmission, hydro and discharge test pressures, and the date of pump and transmission manufacture.

Y__N__

FIRE PUMP WARRANTY - FIVE YEARS

The fire pump shall carry the pump manufacturer's five (5) year warranty covering defective parts and workmanship. A copy of the pump manufacturer's warranty policy shall be provided with the completed apparatus. The warranty shall cover parts for five (5) years and labor for two (2) years.

Y__N__

MECHANICAL SEAL

The pump shall include a mechanical seal.

Y__N__

AKRON VALVES

All suction and discharge valves, including tank to pump lines, will be AKRON brand.

Y__N__

U. L. TEST PLUGS

Two U. L. test plugs shall be pump panel mounted for UL testing of vacuum and pressures.

Y__N__

U. L. TEST - 1750 GPM

The pump will meet and perform the following test to receive a U. L. certification.

- 100% of rated capacity at 150 PSI net pump pressure.
- 100% of rated capacity at 165 PSI net pump pressure.
- 75% of rated capacity at 200 PSI net pump pressure.
- 50% of rated capacity at 250 PSI net pump pressure.

Y__N__

PUMP ANODES

Three (3) sacrificial anodes shall be installed in the pump as follows:

- Intake manifold - two (2)
- Discharge manifold - one (1)

The anodes shall be drilled to indicate that they should be replaced when they leak.

CLARE FIRE DEPARTMENT

Y__N__

FIRE PUMP MULTI-LOCATION PRIMING SYSTEM – TWO LOCATION

A Trident Model #31.001.11 multi-location air operated priming system shall be installed. The unit shall be of all brass and stainless steel construction and designed for fire pumps of 1,250 GPM (4,690 LPM) or more. Due to corrosion exposure no aluminum or vanes shall be used in the primer design. The primer shall be three-barrel design with ¾" NPT connection to the fire pump.

The primer shall be mounted above the pump impeller so that the priming line will automatically drain back to the pump. The primer shall also automatically drain when the panel control actuator is not in operation. The inlet side of the primer shall include a brass 'wye' type strainer with removable stainless steel fine mesh strainer to prevent entry of debris into the primer body.

Performance, Safety, and NFPA Compliance

The priming system shall be capable to a vertical lift to 22 inches of mercury and shall be fully compliant to applicable NFPA standards for vertical lift. The system shall create vacuum by using air from the chassis air brake system through a three-barrel multi-stage internal "venturi nozzles" within the primer body. The noise level during operation of the primer shall not exceed 75 Db.

Air Flow Requirements

The primer shall require a minimum of 15.6 cubic foot per minute air compressor and shall be capable of meeting drafting requirements at high idle engine speed. The air supply shall be from a chassis supplied 'protected' air storage tank with a pressure protection valve. The air supply line shall have a pressure protection valve set between 70 to 80 PSIG.

Primer Controls

The pump primer control shall have a manually operated, panel mounted "push to prime" air valve; which will direct air pressure from the air brake storage tank to the primer body. To prevent freezing, no water shall flow to and from the panel control.

One (1) additional "push to prime" remote primer control shall be installed on the panel for the specified additional intake. The additional control shall operate the air primer to pre-prime and may be used to remove air from the auxiliary intake piping and hose, while the fire pump is operating.

Power Requirements

To reduce the electrical power requirements on the fire apparatus the priming system shall be air powered. The system shall not require annual tear-down and maintenance, an electric motor or solenoid, electrical wiring, lubrication, belt drive, or clutch assembly.

Warranty

The primer shall be covered by a five (5) year parts warranty.

CLARE FIRE DEPARTMENT

ENGINE COOLER

Y__N__

An engine cooler shall be installed inline with the discharge side of the pump. Coolant inlet and outlet shall be continuous, preventing intermixing of engine coolant and pump water.

PUMP COOLER

Y__N__

A pump cooler recirculating line and valve shall be installed. It shall be connected to the discharge side of pump to a valve located on pump panel and back to inlet side of pump.

PUMP HEAT PAN

Y__N__

There shall be one (1) removable heat pan installed under the pump. The pan shall be made from aluminum sheet.

PUMPHOUSE HEATER

Y__N__

A pump house 25,000 BTU heater will be installed behind the pump panel. It will provide warm air flow via forced air, fed from the vehicle cooling system. A fan motor will be installed, switched from the pump panel.

Two valves will be provided in the lines to allow the system to be shut off during warm weather operations.

EVACUATION HORN

Y__N__

There shall be an air horn switch installed on the pump panel that shall activate the chassis air horns.

PUMP SHIFT

Y__N__

A power shift shall be installed in a convenient location to engage fire pump. Two indicator lights located next to the pump shift controls shall be installed. One shall indicate that the pump shift has been successfully completed. The other will indicate that the pump is engaged, the chassis transmission is in pump gear, and the parking brake is engaged.

A "Throttle Ready" indicator light shall be provided at the pump operator's panel that indicates the apparatus is in "OK to Pump" mode.

Location: Left hand side of center dash switch panel

PUMP SHIFT INDICATOR

Y__N__

A green light to indicate that the pump is in gear shall be mounted on the cab dash and on the pump panel.

CLARE FIRE DEPARTMENT

Y__N__

PUMP PRESSURE GOVERNOR

A Fire Research PumpBoss series PBA404-DOO pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor and cables. The control module case shall be waterproof and have dimensions not to exceed 6-3/4" high x 4-5/8" wide x 1-1/2" deep. The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1-3/4" from the front of the control module. Inputs for monitored information shall be from a J1939 databus or independent sensors. Outputs for engine control shall be on the J1939 databus or engine specific wiring. Inputs to the control module from the pump discharge and intake pressure sensors shall be electrical.

The following continuous displays shall be provided:

- Engine RPM: shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LED's
- Oil pressure: shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature: shown on a dual color (green/red) LED bar graph display
- Transmission Temperature: shown on a dual color (green/red) bar LED bar graph display
- Battery voltage: shown on a dual color (green/red) LED bar graph display
- Pressure and RPM operating mode LED's
- Pressure / RPM setting: shown on a dot matrix display
- Throttle ready LED

The dot matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operations.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

- High Battery Voltage
- Low Battery Voltage (engine off)
- Low Battery Voltage (engine running)
- High Transmission Temperature
- Low Engine Oil Pressure
- High Engine Coolant Temperature
- Out of Water (visual alarm only)
- No Engine Response (visual alarm only)

The program features shall be accessed via push buttons located on the front of the control module. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle

CLARE FIRE DEPARTMENT

ready LED shall light when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 PSI. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The PumpBoss shall be located on the driver's side pump panel door.

Y__N__

FOAMPRO 2001 DETAILED SPECIFICATIONS

The apparatus shall be equipped with an electronic, fully automatic, variable speed, direct injection, and discharge side foam proportioning system. The system shall be capable of handling Class A foam concentrates and most Class B foam concentrates. The foam proportioning operation shall be based on direct measurement of water flows, and remain consistent within the specified flows and pressures. System must be capable of delivering accuracy to within 5% of calibrated settings over the advertised operation range when installed according to factory standards. The system shall be equipped with a digital electronic control display suitable for installation on the pump panel. Incorporated within the control display shall be a microprocessor that receives input from the system flowmeter(s), while also monitoring foam concentrate pump output. This compares values to ensure that the operator's preset is proportional to the amount of foam concentrate injected into the discharge side of the fire pump.

Paddlewheel-type flowmeter(s) shall be installed in the discharges specified to be "foam capable." When the use of more than one flowmeter is required, an interface electronics module will be provided to totalize these flows and send the flow total to the microprocessor in the computer control display.

The digital computer control display shall enable the pump operator to perform the following control and operation functions for the foam proportioning system:

- Provide push-button control of foam proportioning rates from 0.1% to 10.0%, in 0.1% increments
- Show current flow-per-minute of water
- Show total volume of water discharged during and after foam operations are completed
- Show total amount of foam concentrate consumed
- Simulate flow rates for manual operation
- Perform setup and diagnostic functions for the computer control microprocessor
- Flash a "low concentrate" warning when the foam concentrate tank(s) runs low
- Flash a "no concentrate" warning and shut the foam concentrate pump off, preventing damage to the pump, should the foam tank(s) empty

A 12 or 24-volt electric motor drive positive displacement foam concentrate pump, rated up to 2.5 gpm (9.5 L/min) @ 150 psi with operating pressures up to 400 psi (27.6 BAR), shall be installed in a suitable, accessible location. The system will draw a maximum of 40 amps @ 12 VDC or 21 amps @ 24 VDC. A pump motor electronic driver (mounted to the base of the pump) shall receive signals from the computer control display and power the 1/2 hp (0.40 Kw) electric motor directly coupled to the concentrate pump in a variable speed duty cycle to ensure that the correct proportion of concentrate preset by the pump operator is injected into the water stream.

CLARE FIRE DEPARTMENT

Full flow check valve shall be provided to prevent foam contamination of fire pump and water tank or water contamination of foam tank.

Components of the complete proportioning system shall include:

Operator control and display
Paddlewheel flowmeter(s)
Pump and electric motor/motor driver
Wiring harnesses
Low level tank switch
Foam tank(s)
Foam injection check valve
Main waterway check valve

An installation and operation manual shall be provided for the unit, along with a one-year limited warranty by the manufacturer. The system must be installed and calibrated by a Certified FoamPro Dealer.

The system design shall have passed environmental testing which simulates heavy use on off-road mobile apparatus. Testing shall have been conducted in accordance to SAE standards.

Foam Locations: Front bumper discharge, (2) 1-3/4" crosslays, booster reel

Y__N__

FOAM REFILL PUMP - TRUCK MOUNTED

A truck mounted FomPro foam system refill shall be supplied and installed.

System includes:

- High-capacity concentrate pump
- Continuous-duty 12 or 24-volt motor
- Electronic microprocessor control
- Flush valve
- Indicator lights
- Panel plates
- Stainless fittings and cap
- 1" concentrate pick-up wand
- Check valves
- 6' of one inch hard suction hose with wand

Y__N__

STAINLESS PLUMBING

All plumbing shall be either stainless steel or high pressure hose with crimped stainless steel fittings. Any manifolds shall be stainless steel. All valves shall be bronze or stainless steel unless other specified.

CLARE FIRE DEPARTMENT

STAINLESS PLUMBING WARRANTY - TEN YEARS

Y__N__

The manufacturer warrants to the original purchaser all stainless steel plumbing components installed by them and used in the construction of the apparatus water / foam plumbing systems against defects in workmanship and materials for a period of ten (10) years from delivery.

TANK TO PUMP

Y__N__

A 3" full flow valve shall be installed between the tank and pump suction. Control will be with a direct link control rod.

MASTER PUMP DRAIN

Y__N__

The master drain shall have the capacity to drain all lines and main pump at the same time. The master drain will be mounted on the pump panel and will be readily accessible.

LINE DRAINS

Y__N__

All suction and discharge lines (1-1/2" and larger) shall have a lever action quarter turn drain valve installed. Each drain valve shall be arranged adjacent to the valve or in a convenient location on the left and/or right pump panel. Remote drain lines will be clearly marked with color coded tags.

INTAKE RELIEF VALVE

Y__N__

A stainless steel suction relief valve will be installed on the suction port of the main fire pump. The valve will be adjustable from 75-250 PSI. The valve will terminate at a 2-1/2" NST-M flange; a cap will be available for emergency use.

PUMP TO TANK LINE

Y__N__

There shall be a 2" pump to tank fill line installed with a 2" inline valve. The valve shall be controlled from the pump panel.

1-3/4" FRONT JUMP LINE

Y__N__

There shall be a 2" jump line installed with a 2" inline valve. The valve shall be controlled at the pump panel. The rigid piping will be stainless steel with flexible high pressure hydraulic hose lines using stainless steel fittings. There will be a 2" swivel elbow with 1-1/2" NST threads.

JUMLINE SWIVEL

Y__N__

The front jumpline swivel will be installed on the gravelshield on the driver side adjacent to the hosewell.

CLARE FIRE DEPARTMENT

6" STEAMER INLETS (2)

Y__N__

Two (2) 6" steamer inlets will be provided, one (1) left side and one (1) on right side.

The driver side shall include a chrome cap.

HIGH FLOW BALL INTAKE VALVE

Y__N__

A TFT Ball Intake Valve (BIV) shall be provided and installed on the right side steamer inlet of the pump.

Task Force Tips model #AX1ST-NX manually operated lightweight aluminum high flow ball intake valve shall be provided. The unit shall be equipped with an adjustable pressure relief valve under the main valve body with an eight position adjustable inlet elbow. The valve shall be controlled with an NFPA compliant slow-close hand wheel gear operator which can be configured for left or right hand operation. A 3/4" bleeder valve shall be provided to exhaust excess air or water from the valve and hoseline. A position indicator shall be provided to allow for quick visualization of the status of the valve in the open, closed or partial positions. For maximum corrosion protection the aluminum casting shall be hardcoat anodized, with a powder coat internal and external finish and all components facing the wet side of the valve shall be constructed from stainless steel.

The connections shall be: 5" Storz rigid with 30 degree swiveling detent elbow and a 6" female NH swivel long handle connection and include polymer bearing strips for prevention of galvanic corrosion. The Storz coupling shall be easily configurable as swivel or rigid with a tool. The unit shall have a unique serial number and be covered by a five-year warranty.

LEFT 2-1/2" SUCTION INTAKE

Y__N__

A 2-1/2" ball-type suction valve shall be installed on the left side pump panel with the valve body mounted behind the pump panel. The control shall be a fixed pivot design, with the handle located along side the suction valve.

The suction valve shall come equipped with a chrome plug, chain, brass inlet strainer and a 2-1/2" NST chrome inlet swivel.

LEFT 2-1/2" DISCHARGES (2)

Y__N__

Two (2) 2-1/2" discharge shall be located on the left side pump panel. The valve shall be a quarter turn ball type and fixed pivot design to allow easy operation at all pump pressures, and operated from the panel. The threads on the valve shall be 2-1/2" NST. The discharge shall come equipped with a 3/4" drain valve.

DISCHARGE ADAPTER

Y__N__

A chrome 30 degree elbow, cap and chain shall be supplied with the discharge(s).

CLARE FIRE DEPARTMENT

RIGHT 2-1/2" DISCHARGE (1)

Y__N__

One (1) 2-1/2" discharge shall be located on the right side pump panel. The valve shall be a quarter turn ball type and fixed pivot design to allow easy operation at all pump pressures, and operated from the panel. The threads on the valve shall be 2-1/2" NST. The discharge shall come equipped with a 3/4" drain valve.

DISCHARGE ADAPTER

Y__N__

A chrome 30 degree elbow, cap and chain shall be supplied with the discharge(s).

4" RIGHT PANEL LD DISCHARGE - 3" VALVE

Y__N__

There shall be a 4" discharge on the right pump panel. The discharge shall be piped to the discharge side of the pump through a 3" valve that shall be pump panel controlled. A 3/4" quarter turn drain valve shall be installed.

DISCHARGE ELBOW

Y__N__

The following elbow shall be supplied for the discharge(s):

4" NH-F x 5" storz 30 degree elbow

DECK GUN DISCHARGE - 3" - HANDWHEEL CONTROLLED

Y__N__

There shall be a 3" deck gun discharge pipe installed above the pump compartment.

The discharge shall be a gear actuated valve controlled by a handwheel on the pump panel. The discharge shall terminate with a 4-bolt flange.

SLO-CLOSE VALVES

Y__N__

A SLO-CLOSE feature will be installed on all valves over 2-1/2" in size as directed by NFPA. These valves will allow full open and close functions without water hammer.

2-1/2" CROSSLAY HOSEBED

Y__N__

One (1) 2-1/2" crosslay shall be installed on top of the pump house. The crosslay shall hold 200' of 2-1/2" double jacket fire hose. A 2-1/2" mechanical swivel hose connector shall be used in the crosslay to provide access of hose in either direction.

The crosslay shall have one 2-1/2" valve and shall be controlled with a 1/4 turn locking handle mounted on the pump panel.

CLARE FIRE DEPARTMENT

CROSSLAY HOSEBED COVER

Y__N__

There shall be an aluminum cover for the crosslays. The cover shall be constructed of 1/8" aluminum tread plate and be hinged with a stainless steel knuckle hinge. The cover shall open from the front of the body and swing up to the rear of the body.

CROSSLAY FLAPS

Y__N__

Side flaps for crosslays constructed of 22 ounce hypalon shall be installed to retain hose in the pre-connected beds per NFPA requirements.

1-3/4" SPEEDLAY HOSEBED (2)

Y__N__

Two (2) speedlays shall be installed ahead of the pump module. Each speedlay shall hold 200' of 1-3/4" double jacket fire hose. A 2" mechanical swivel with 1-3/4" NST threads shall be used in the speedlay to provide access of hose in either direction. The speedlay section shall have one 2" valve and shall be controlled with a handle mounted on the pump panel.

SPEEDLAY FLAPS

Y__N__

Side flaps for speedlays constructed of 22 ounce hypalon shall be installed to retain hose in the pre-connected beds per NFPA requirements.

HOSELAY CARTRIDGES (4)

Y__N__

Four (4) poly hoselay cartridges will be provided with the apparatus.

DUNNAGE

Y__N__

A dunnage area will be provided over the pump house for storage of equipment. The area will be four sided with an open top design.

BOOSTER REEL PLUMBING

Y__N__

There shall be a 1-1/2" inline valve installed between the pump and the booster reel. The valve shall be controlled from the pump panel. A 1-1/2" flexible high pressure hose shall be installed between the valve and hose reel.

BOOSTER REEL

Y__N__

A Hannay booster reel with painted disc shall be installed as directed. The reel shall be constructed utilizing a welded base. The rewind will be a 12-volt electric motor and will chain drive the reel drum. The booster reel shall have an automatic brake to prevent the booster hose from unwinding. Reel shall have a capacity for **200'** of **1"** booster hose.

CLARE FIRE DEPARTMENT

Two (2) fully shielded, rewind switches shall be provided in a convenient location, one (1) each side of the pump module . A gear driven manual rewind shall be included. The booster reel discharge control shall be located at the operator's control panel.

Location: Pump dunnage

Y__N__

BOOSTER REEL ROLLERS / GUIDES

Two (2) sets of stainless steel rollers with guides shall be furnished for the booster reel as directed by the customer.

Location: One (1) above each side of pump module

Y__N__

BOOSTER HOSE

There shall be two (2) lengths of 1" x 100' non collapsing hose with 1" NST couplings supplied, total of 200'. The hose shall be Niedner Reeltex.

Y__N__

NOZZLE WITH SHUTOFF

Task Force Tips model # DS1040P ball shut off nozzle shall be provided. The selectable, dual gallonage nozzle shall be furnished with flow settings of 10 and 40 GPM at 100 PSI and produce fog and straight stream patterns. The nozzle body shall be constructed from hardcoat anodized aluminum alloy, utilize a stainless steel ball shut off valve with a quick change polymer valve seat. An integral pistol grip handle shall be positioned directly below the valve handle. This nozzle shall have a "twist off" position for positive shut off. The nozzle shall be furnished with a 1" female NH swivel rocker lug inlet and designed to accept the Task Force Tips FJ-MX-D FoamJet foam aspirating attachment. The unit shall have a unique serial number and be covered by a written five-year warranty.

Location: Driver side pump panel with PAC mount

Y__N__

BOOSTER REEL BLOWOUT VALVE

A booster reel blow out valve shall be supplied and installed.

Y__N__

REAR SUCTION

There shall be a rear suction that will mount horizontally through the rear of the apparatus. The suction shall use 5" STAINLESS steel pipe and shall extend from the right rear to the right suction side of pump. A 6" NST adapter with chrome plated cap will be furnished. The valve shall be an electrically actuated butterfly with a built-in relief valve and air bleeder. Switch controls shall be located on the pump panel.

A manual override shall be located at the valve. A chrome NST adapter and long handle cap shall be included.

Location: Right rear below ground ladders

CLARE FIRE DEPARTMENT

REAR SUCTION WARNING PLATE

Y__N__

A permanent plate shall be installed at the rear indicating "BLEED SUCTION LINE BEFORE REMOVING CAP - DEATH OR SERIOUS INJURY MAY RESULT FROM IMPROPER OPERATION".

REAR SUCTION DRAIN CONTROL

Y__N__

There shall be a 1/4 turn drain valve for the rear suction that will be controlled near the right side running board.

REAR SUCTION DRAIN

Y__N__

There shall be a 1/4 turn drain valve for the rear suction at the rear of the apparatus, adjacent to the inlet.

2-1/2" REAR DISCHARGE

Y__N__

A 2-1/2" rear discharge shall be provided using a 2-1/2" stainless steel pipe with a chrome 2-1/2" male NST adapter on the outside end. Rear discharge shall be operated by a 2-1/2" valve with T-handle controls on the pump panel. Discharge shall have a 3/4" drain valve.

DISCHARGE ADAPTER

Y__N__

A chrome 30 degree elbow, cap and chain shall be supplied with the discharge(s).

REAR DISCHARGE SLEEVE

Y__N__

A 4" diameter special pass-through sleeve shall be installed in the tank for the installation of a rear discharge.

TANK FILL - 4" FIREMAN'S FRIEND - REAR

Y__N__

There shall be a 4" Fireman's Friend semi-automatic fill valve with a 4" NPT-F fitting installed at the rear of the apparatus. The valve is a stainless steel internally mounted check-type fill valve. Inlet adapters are not included with this item.

FIREMANS FRIEND WARNING PLATE

Y__N__

A permanent plate shall be installed near the fireman's friend indicating "DO NOT EXCEED 100 PSI".

CLARE FIRE DEPARTMENT

FAST FILL DIFFUSER

Y__N__

A fast fill fitting with a diffuser shall be installed in the water tank.

ADAPTER

Y__N__

The following adapter shall be supplied for the rear tank fill:

4" NPT-M x 2-1/2" NHF swivel w/ plug

TANKER VENT

Y__N__

A 6" vent shall be installed in lieu of standard size.

MASTER PRESSURE GAUGE

Y__N__

There shall be one (1) 4-1/2" silicone filled gauge that will have a 316 stainless steel bezel. The gauge will read from 0 to 400lb and will be accurate to within 1%. The gauge shall be located on the pump panel and placed in a well lighted position for night apparatus operation.

MASTER INTAKE GAUGE

Y__N__

There shall be one (1) 4-1/2" silicone filled gauge that will have a 316 stainless steel bezel. The gauge will read from 30" to 400lb and will be accurate to within 1%. The gauge shall be located on the pump panel and placed in a well lighted position for night apparatus operation.

DISCHARGE PRESSURE GAUGES

Y__N__

Each discharge shall include a 2-1/2" silicone filled gauge that will have a 316 stainless steel bezel. The gauge face will be white and have black markings. The gauge will read 0 to 400lb and will be accurate to within 1%. The gauge shall be located on the pump panel and placed in a well lighted position for night apparatus operation.

POLYPROPYLENE WATER TANK

Y__N__

The booster tank shall have a capacity of 1200 US gallons.

CONSTRUCTION:

The water tank shall be constructed of polypropylene or Polyrene sheet stock. This material shall be a non-corrosive thermo plastic.

The booster and/or foam tank shall be of a specific configuration and is so designed to be completely independent of the body and compartments. The tank shall be constructed utilizing latest thermo plastic welding technology. The tank shall undergo extensive

CLARE FIRE DEPARTMENT

testing prior to installation in the truck. In addition, the completed tank shall be water pressure tested. Baffles, both longitudinal and latitudinal shall be interlocking and thermo welded to minimize water surge during travel, enhancing road handling stability. Openings in the baffles shall be positioned to allow water flow to NFPA standards during filling or pumping operations. The tank shall be mounted on hard rubber cushions to isolate the tank from road shock and vibrations. The tank shall be mounted according to manufactures recommendations. The tank shall be completely removable without disturbing or dismounting the apparatus body structure. A lifetime manufacturer's statement of Warranty shall warrant each tank to be free from manufacturing defects in material and workmanship for the service life of the vehicle.

FILL TOWER AND COVER:

The tank shall have a combination vent and manual fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the customer. The tower shall have a 1/4" thick removable polypropylene screen and a hinged cover. Inside the fill tower approximately 4" down from the top shall be fastened a combination vent overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with a minimum I. D. of 4" that is designed to run through the tank and shall be piped behind the rear wheels to maximize traction.

SUMP:

There shall be one (1) sump standard per tank. On tanks that require front suction, 4" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" NPT threaded inlet on the bottom for a drain plug. This shall be used as a combination clean out and drain.

OUTLETS:

There will be two (2) standard tank outlets: One for tank to pump suction line which shall be a minimum of 3" NPT coupling; and One for a tank fill line which shall be a minimum of 2" NPT coupling. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank.

DESIGN:

The tank shall be designed to include the hosebed, storage sleeves and any upper body compartments. The entire hosebed, tank and upper body storage shall be able to be removed with one set of lifting eyes.

POLYPROPYLENE TANK WARRANTY - LIFETIME

The water tank manufacturer shall warrant the booster/foam tank to be free from manufacturing defects in material and workmanship for the service life of the vehicle. The tank must be installed in accordance with tank manufacturer's installation recommendations.

A copy of the tank manufacturer's warranty, including terms and limitations will be provided upon delivery of the completed apparatus.

Y__N__

CLARE FIRE DEPARTMENT

WATER TANK LEVEL GAUGE

Y__N__

A FRC Tank vision water level display with ultra-brite LED display shall be installed. A single pressure transducer shall be installed in the main water tank.

WATER TANK LEVEL GAUGE

Y__N__

There shall be a FRC MaxVision water level LED strip light(s) provided and installed. The gauge has LED lights of different colors and operates off the master water level gauge.

Location(s): Rear of body, Two (2) shall be cab supplied

INTERNAL FOAM CELL - CLASS "A"

Y__N__

There shall be a 30-gallon minimum capacity internal foam tank incorporated in the main water tank. The tank shall have an access hole for filling and cleaning and a discharge outlet.

CLASS "A" FOAM PLATES

Y__N__

A permanent plate identifying the foam cell contents as class "A" shall be placed on the top and on the inside of the lid for positive identification.

FOAM TANK LEVEL GAUGE

Y__N__

A FRC Tankvision Foam tank level display with ultra-brite LED display shall be installed on the apparatus. A single pressure transducer shall be installed in the foam tank. A foam tank vent shall be installed in the fill tower.

HOSEBED

Y__N__

The hose body will be constructed from smooth plate aluminum. The upper edges will be 2" x 3" hollow aluminum extrusions, with smooth aluminum for the inside surface. 1/8" (.125) 3003 H-14 smooth aluminum will be installed for the hosebed walls and serve as a drip cap on top of the body sides. The hose compartment floor will be constructed from a ribbed co-polymer polypropylene. The hose body floor ends will be slotted to allow for infinite adjustment of the hose bed dividers. The hosebed floor shall be constructed as part of the tank.

The 16" deep hosebed shall include a 20" open walkway running from the front of the body to the rear of the apparatus for safely loading and unloading equipment and hose.

CLARE FIRE DEPARTMENT

Y__N__

ALUMINUM HOSEBED COVERS

Two (2) aluminum tread plate hose bed covers shall be provided, one (1) each side of the open walkway. Covers shall be two-door type with continuous stainless steel hinge along each side. Cover doors shall have gas assist cylinders for ease of opening.

Y__N__

HOSEBED DIVIDERS

Three (3) hose bed dividers manufactured from 3/16" smooth aluminum plate with an extruded aluminum base welded to the bottom shall be provided. The dividers shall have an extruded track to slide in to allow the hose bed to be adjusted for different hose capacities. One end of each divider shall have a 3" radius corner with a hand hole cutout provided. The dividers shall be sanded as to prevent damage to hose.

Note: Two (2) of the dividers will be located at the edges of the walkway and will be used for the hosebed covers resting spot, they will not be adjustable.

Y__N__

EXTRUDED ALUMINUM BODY AND SUPERSTRUCTURE

The body subframe is to be entirely welded, constructed of 6061-T6 extruded aluminum tubing with **minimum** dimensions of 3"x3"x3/8", 2"x3"x1/4" and 1"x3" solid. All vertical components are to be reinforced to the substructure with 2"x3"x1/4" 6061-T6 TUBULAR gussets at strategic points to assure structural integrity.

The body sides are to be constructed from 2"x3"x1/4" 6061-T6 structural aluminum tubing welded to form a continuous support matrix for the hose body and compartments. The interior components will be welded along perimeter and along each side for additional support.

The upper body side panels shall be constructed with a single sheet to present a seamless construction and maximum corrosion protection.

The tank cradle will be designed to support the bottom of the water tank to prevent movement and structural damage when the unit is loaded and under motion. Reinforced rubber pads with a 60# rating will be installed in the cradle and at the corner angles to cushion the tank; no mechanical attaching devices will protrude through the rubber. Multiple 1-3/4" x 2" solid bar shall be welded into the sub frame for the tank mounting brackets. The tank shall be mounted according to manufactures recommendations.

Fender liners will be independent from the compartment sides to provide maximum corrosion and impact protection. Wheelwell fastening support angles shall be welded and be made from 1" x 1" x 1/4" angle.

The apparatus body shall be entirely independent from the chassis frame. It is to be attached to the frame over 1/2" x 3" 60# rubber pads running the full length of body. The unit is to be designed so as to be removable from the chassis in the event of future chassis replacement.

CLARE FIRE DEPARTMENT

Y__N__

EXTRUDED ALUMINUM APPARATUS BODY

The 100" wide apparatus body compartments are to be constructed from 3/16" aluminum alloy. All compartments are to be formed and welded to the substructure and sidewalls. Lower compartment floors are to be fitted with hat section supports to allow for loading of heavy equipment. The back side of the compartments shall be fitted with hat sections to allow for additional support and to act as a spacer for the installation of the water tank.

COMPARTMENTATION:

Each compartment shall be "sweep-out" style. The compartments shall not share a common wall and shall be individually vented. The compartments shall be divided as follows:

SIDE:

There shall be two (2) compartments ahead of the rear wheels, one (1) each side. The compartments shall be approximately **60" wide x 60" high x 14/26" deep**.

There shall be two (2) compartments over the rear wheels, one (1) each side. The compartments will be approximately **58" wide x 28" high x 14" deep**.

There shall be two (2) compartments behind the rear wheels, one (1) each side. The compartments shall be approximately **52" wide x 60" high x 26" deep**.

REAR:

There shall be one (1) compartment in the rear of the apparatus. The compartment shall be approximately **32" wide x 33" high x 24" deep**.

Y__N__

SUPERSTRUCTURE AND BODY WARRANTY - LIFETIME

The manufacturer shall warrant to the original purchaser that the apparatus superstructure and body is structurally sound and free of all structural defects of workmanship and material and further warrants that it will maintain its structural integrity for the life of the apparatus. This warranty shall not pertain to issues of paint finish, hardware, moldings or accessories. The warranty shall terminate upon transfer of possession or ownership by the original purchaser.

Y__N__

L1 COMPARTMENT

- The following is a description of items included with the compartment.

Y__N__

ROLL UP DOOR - BRUSHED

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

CLARE FIRE DEPARTMENT

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

Y__N__

ROLL UP DOOR SILLS

An extruded aluminum door sill shall be provided for each roll up door.

Y__N__

DOOR STRAP

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

Y__N__

ADJUSTABLE SHELF TRACKING

There shall be tracking installed in one (1) compartment to accommodate the installation of adjustable shelves and/or roll-outs. The tracks shall be installed vertically on the walls of the compartment.

Y__N__

ADJUSTABLE SHELF- SHALLOW DEPTH

There shall be an adjustable shelf made from 3/16" aluminum with 2" sides provided and installed on the adjustable tracking.

Y__N__

ROLL OUT TRAY - FLOOR MOUNTED

A Slide-Master aluminum heavy duty roll-out tray with a minimum capacity of 500# shall be provided and installed on the compartment floor. The tray shall be constructed of 3/16" aluminum with a 2" lip on each side. The roll-out mechanism shall include a push/pull spring lock for the full open and closed positions.

Y__N__

LED COMPARTMENT LIGHTS

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

Y__N__

L2 COMPARTMENT

- The following is a description of items included with the compartment.

Y__N__

ROLL UP DOOR - BRUSHED

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather

CLARE FIRE DEPARTMENT

resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

Y__N__

ROLL UP DOOR SILLS

An extruded aluminum door sill shall be provided for each roll up door.

Y__N__

DOOR STRAP

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

Y__N__

SWING-OUT TOOL BOARD TRACKING

There shall be tracking installed in one (1) compartment to accommodate the installation of swing-out tool boards. The tracks shall be installed horizontally on the walls of the compartment.

Y__N__

VERTICAL SWING-OUT TOOLBOARD

A vertical swing-out toolboard will be installed on the adjustable tracking. The vertical partition shall be made from 3/4" thick co-polymer material. It shall be hinged from one side with a positive latching mechanism on the opposite side.

The unit shall be adjustable with respect to the depth of the compartment.

Y__N__

BACKWALL TOOLBOARD

A toolboard will be installed on the compartment upper back wall. The partition shall be made from 3/4" thick co-polymer material.

Y__N__

LED COMPARTMENT LIGHTS

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

CLARE FIRE DEPARTMENT

L3 COMPARTMENT

Y__N__

The following is a description of items included with the compartment.

ROLL UP DOOR - BRUSHED

Y__N__

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

ROLL UP DOOR SILLS

Y__N__

An extruded aluminum door sill shall be provided for each roll up door.

DOOR STRAP

Y__N__

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

ADJUSTABLE SHELF TRACKING

Y__N__

There shall be tracking installed in one (1) compartment to accommodate the installation of adjustable shelves and/or roll-outs. The tracks shall be installed vertically on the walls of the compartment.

ROLL OUT TRAY - FLOOR MOUNTED

Y__N__

A Slide-Master aluminum heavy duty roll-out tray with a minimum capacity of 500# shall be provided and installed on the compartment floor. The tray shall be constructed of 3/16" aluminum with a 2" lip on each side. The roll-out mechanism shall include a push/pull spring lock for the full open and closed positions.

LED COMPARTMENT LIGHTS

Y__N__

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

CLARE FIRE DEPARTMENT

Y__N__

REAR COMPARTMENT

The following is a description of items included with the compartment.

Y__N__

ROLL UP DOOR - BRUSHED

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

Y__N__

ROLL UP DOOR SILLS

An extruded aluminum door sill shall be provided for each roll up door.

Y__N__

ROLL OUT TRAY - FLOOR MOUNTED

A Slide-Master aluminum heavy duty 100% roll-out tray with a minimum capacity of 500# shall be provided and installed on the compartment floor. The tray shall be constructed of 3/16" aluminum with a 2" lip on each side. The roll-out mechanism shall include a push/pull spring lock for the full open and closed positions.

Y__N__

LED COMPARTMENT LIGHTS

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

Y__N__

R1 COMPARTMENT

- The following is a description of items included with the compartment.

Y__N__

ROLL UP DOOR - BRUSHED

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

CLARE FIRE DEPARTMENT

Lighting will be located on the vertical compartment walls for maximum effectiveness.

Y__N__

ROLL UP DOOR SILLS

An extruded aluminum door sill shall be provided for each roll up door.

Y__N__

DOOR STRAP

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

Y__N__

ADJUSTABLE SHELF TRACKING

There shall be tracking installed in one (1) compartment to accommodate the installation of adjustable shelves and/or roll-outs. The tracks shall be installed vertically on the walls of the compartment.

Y__N__

ADJUSTABLE SHELVES - SHALLOW DEPTH

There shall be two (2) adjustable shelves made from 3/16" aluminum with 2" sides provided and installed on the adjustable tracking.

Location: Rear of vertical divider

Y__N__

ROLL OUT TRAY - FLOOR MOUNTED

A Slide-Master aluminum heavy duty roll-out tray with a minimum capacity of 500# shall be provided and installed on the compartment floor. The tray shall be constructed of 3/16" aluminum with a 2" lip on each side. The roll-out mechanism shall include a push/pull spring lock for the full open and closed positions.

Y__N__

BACKWALL TOOLBOARD

A toolboard will be installed on the compartment upper back wall. The partition shall be made from 3/4" thick co-polymer material.

Location: Forward of vertical divider

Y__N__

VERTICAL COMPARTMENT DIVIDER

A bolt in vertical compartment divider fabricated from 3/16" aluminum shall be provided and installed in the upper shallow depth portion of the compartment.

Location: Centered from side to side unless otherwise noted

CLARE FIRE DEPARTMENT

LED COMPARTMENT LIGHTS

Y__N__

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

R2 COMPARTMENT

Y__N__

- The following is a description of items included with the compartment.

ROLL UP DOOR - BRUSHED

Y__N__

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

ROLL UP DOOR SILLS

Y__N__

An extruded aluminum door sill shall be provided for each roll up door.

DOOR STRAP

Y__N__

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

ADJUSTABLE SHELF TRACKING

Y__N__

There shall be tracking installed in one (1) compartment to accommodate the installation of adjustable shelves and/or roll-outs. The tracks shall be installed vertically on the walls of the compartment.

ADJUSTABLE SHELF- SHALLOW DEPTH

Y__N__

There shall be an adjustable shelf made from 3/16" aluminum with 2" sides provided and installed on the adjustable tracking.

CLARE FIRE DEPARTMENT

LED COMPARTMENT LIGHTS

Y__N__

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

R3 COMPARTMENT

Y__N__

The following is a description of items included with the compartment.

ROLL UP DOOR - BRUSHED

Y__N__

ROM series 4 roll-up door will be installed in this compartment. The shutters will be constructed from extruded aluminum with a brushed finish. Internally sealed for weather resistance and quiet operation. Rubber seals will be installed on the vertical components. The door will close/lock with a combination handle/locking bar on the exterior at the bottom.

The door will roll-up in the top of the compartment to allow for maximum use of the compartment interior.

Lighting will be located on the vertical compartment walls for maximum effectiveness.

ROLL UP DOOR SILLS

Y__N__

An extruded aluminum door sill shall be provided for each roll up door.

DOOR STRAP

Y__N__

An elastic door strap shall be installed on this compartment door to assist in lowering the door.

ADJUSTABLE SHELF TRACKING

Y__N__

There shall be tracking installed in one (1) compartment to accommodate the installation of adjustable shelves and/or roll-outs. The tracks shall be installed vertically on the walls of the compartment.

ADJUSTABLE SHELVES - SHALLOW DEPTH

Y__N__

There shall be two (2) adjustable shelves made from 3/16" aluminum with 2" sides provided and installed on the adjustable tracking.

ROLL OUT TRAY - FLOOR MOUNTED

Y__N__

A Slide-Master aluminum heavy duty roll-out tray with a minimum capacity of 500# shall be provided and installed on the compartment floor. The tray shall be constructed of

CLARE FIRE DEPARTMENT

3/16" aluminum with a 2" lip on each side. The roll-out mechanism shall include a push/pull spring lock for the full open and closed positions.

Y__N__

LED COMPARTMENT LIGHTS

Two (2) extruded aluminum LED strip lights shall be installed in the compartment. The strip lights shall integrate with the ROM door tracks installed in a vertical position and run the full height of the compartment, one (1) each side.

Y__N__

ROLL-UP DOOR WARRANTY - SEVEN YEARS

ROM series 4 doors and parts shall be warranted for a period of seven (7) years.

Y__N__

COMPARTMENT INTERIOR FINISH

All exterior compartments of the pumper/rescue apparatus will be constructed from fire apparatus quality aluminum material. All exterior seams will be welded and sealed from weather and dust. The interior compartment seams will all be carefully caulked with a gray sealant for further protection and cosmetics.

The apparatus compartment interiors will be polished aluminum diamondplate.

Y__N__

RUBRAILS

Poly rub rails shall be provided along the lower edge of the apparatus body. The rub rail assemblies shall be spaced-out and isolated from the body with non-metallic materials. Each rub rail shall be a minimum of 1" thick and tapered at each end.

Y__N__

BODY FACE PACKAGE

The front face of the apparatus body will be trimmed with 1/8" polished diamondplate aluminum. Body support extrusions will be drilled and tapped for application of stainless steel fasteners to hold the panels in place. The panels are to be easily removable for service.

The rear face of the body will be trimmed with 1/8" smooth plate aluminum to allow easy application of chevron material.

All exterior edges will be sanded and rounded to prevent the catching of equipment or any injuries. The exterior seams shall be carefully caulked for water prevention and cosmetics.

Y__N__

REAR TAILBOARD

An 11" rear tailboard step will be provided. The step will be constructed from 1-1/2" extruded aluminum. Extrusion shall have a non-slip surface with punched holes. Tailboard shall be supported by heavy 2" x 2" x 3/8" angles welded directly to the body superstructure.

CLARE FIRE DEPARTMENT

REAR WHEELWELL TRIM

Y__N__

The area around the rear wheel openings shall be constructed from aluminum diamondplate. The wheelwells shall be completely removable for ease of service and replacement.

POLISHED FENDERETTES

Y__N__

Polished fenderettes shall be installed on the rear wheelwells. They shall be bolted so as to be easily removable for service and/or replacement.

MUDFLAPS

Y__N__

Mud flaps shall be made from black hard rubber and shall be installed on the cab fenders, behind the front tires and on the body fenders, behind the rear tires.

MISCELLANEOUS HARDWARE

Y__N__

One bag of miscellaneous hardware shall be supplied with the finished apparatus. This hardware shall consist of nuts, bolts, screws, washers, etc. used in the manufacture of the apparatus.

FUEL INLET

Y__N__

There shall be a cast aluminum bezel around the fuel inlet. The bezel will be clearly marked "DIESEL FUEL ONLY".

SCBA BOTTLE STORAGE

Y__N__

Four (4) single SCBA bottle storage compartments shall be located in the rear wheel well area. The compartments shall be fabricated from an 8" diameter vacuum poly tube. The tubes will be supported at the opening by a formed flange bolted to the body. The bottom of each tube is also to be supported to eliminate breakage from vibration. The tubes are vented to facilitate moisture drainage. The compartment doors shall be a brushed stainless steel door secured by a positive latch.

GROUND LADDER STORAGE

Y__N__

The apparatus shall be equipped with a ground ladder storage compartment configured through the polypropylene tank.

Access to the compartment shall be a hinged door, located at the rear of the apparatus.

CLARE FIRE DEPARTMENT

Y__N__

SUCTION HOSE STORAGE

The apparatus shall be equipped with a suction hose storage compartment configured through the polypropylene tank. The compartment will accommodate one (1) of the suction hoses with a pre-connected strainer. The additional piece of suction hose shall be located in the hosebed.

Access to the compartment shall be a hinged door, located at the rear of the apparatus.

PIKE POLE STORAGE

Y__N__

The pike poles shall be stored in tubes fabricated into the tank.

Access to the compartment shall be a hinged door, located at the rear of the apparatus.

LIGHTED FOLDING STEPS - FRONT - DRIVER SIDE

Y__N__

There shall be four (4) cast folding steps mounted as required on the front driver side of the apparatus body. The steps will be NFPA compliant. Each step shall include an LED light to light up the top of the step and another LED light to light up the area below the step. The lights will be activated with the parking brake.

LIGHTED FOLDING STEPS - FRONT - PASSENGER SIDE

Y__N__

There shall be four (4) cast folding steps mounted as required on the front passenger side of the apparatus body. The steps will be NFPA compliant. Each step shall include an LED light to light up the top of the step and another LED light to light up the area below the step. The lights will be activated with the parking brake.

REAR BODY ACCESS LADDER

Y__N__

A rear access ladder shall be made of 100% stainless steel and poly. The ladder will be installed on the back of the apparatus for access to the upper body walkway or hose bed. The ladder shall swing out and fold down for a natural climbing angle. The ladder folds up and stores against the body. The handrails are 1-1/2" poly with NFPA slip resistant testing.

INTERMEDIATE REAR STEP WITH GRAB HANDLES

Y__N__

An intermediate rear step will be provided at the rear of the apparatus for easy access to the top of the body. The step will be constructed from an open grip strut aluminum material or NFPA compliant diamondplate aluminum and bolted to extrusions in the structure of the apparatus body.

The intermediate rear step shall include laser cut hand holes to assist in climbing. The holes shall be large enough for a gloved hand and be located on each side of the step.

CLARE FIRE DEPARTMENT

Y__N__

REAR BODY HANDRAILS

There shall be one (1) 30" long handrails manufactured from 1-1/4" diameter extruded aluminum with chrome end stanchions. It shall be mounted vertically at the rear of the apparatus body.

In the event there is telescoping scene light, ladder or folding step installed in the same location(s), these items may be substituted in an effort to conserve mounting space on the body.

Y__N__

REAR TOP BODY HANDRAIL

There shall be one (1) 1-1/4" diameter extruded aluminum handrail installed at the top of the apparatus body to assist in entering and exiting the hosebed. The hand rail shall be supported with chrome stanchions.

In the event there is telescoping scene light, ladder or folding step installed in the same location(s), these items may be substituted in an effort to conserve mounting space on the body.

Y__N__

FRONT OF BODY HANDRAILS

There shall be two (2) handrails manufactured from 1-1/4" diameter extruded aluminum with chrome end stanchions. They shall be mounted horizontally at the front of the apparatus body to assist in climbing the front steps.

In the event there is telescoping scene light, ladder or folding step installed in the same location(s), these items may be substituted in an effort to conserve mounting space on the body.

Y__N__

ALUMINUM BODY PAINT FINISH

All paintable surfaces shall conform to the following procedure, ensuring a durable finish:

- Aluminum body exterior shall not have components mounted to paintable surfaces prior to application of protective anti-corrosion and topcoat refinish materials.
- All paintable aluminum surfaces shall be sanded/ground to remove all burrs, rough edges and other imperfections from the fabrication process.
- All paintable metal surfaces shall have an anti-corrosion coating and an epoxy-based primer applied to them before the application of body fillers.
- After application and finishing of all filler work, any bare metal areas shall be recoated with an anti-corrosion coating and an epoxy-based primer before continuing the refinish process.
- The unit shall be sprayed with a high quality urethane primer-surfacer. The primer-surfacer shall be sanded to provide a smooth appearing surface that

CLARE FIRE DEPARTMENT

will facilitate adhesion of a urethane-based sealer. The urethane-based sealer shall be applied in such a manner to provide a uniform surface for the application of subsequent topcoats. The apparatus body shall be top-coated with basecoat/clear coat polyurethane paint system. The finished paint surface shall have a high gloss- >85 using a 60° gloss meter.

- Any location where aluminum is penetrated after the refinish process has been completed, shall be treated with a corrosion inhibiting compounds.

Y___N___

PAINT WARRANTY - TEN YEARS

The paint performance guarantee will cover the areas of the vehicle finished with the specified product for a period of ten (10) years beginning the day the vehicle is delivered to the purchaser.

The areas as outlined on the Guarantee Certificate will be covered for the following paint failures:

GUARANTEE INCLUSIONS:

FULL APPARATUS BODY MANUFACTURED AND PAINTED BY THE MANUFACTURER:

- Peeling or de lamination of the topcoat and/or other layers of paint.
- Cracking or checking.
- Loss of gloss caused by cracking, checking, or hazing.
- Any paint failure caused by defective finishes which are covered by this guarantee.

All guarantee exclusions, limitations, and methods of claims are covered in the full certificate provided to the original purchaser.

The paint warranty is a full term (non-prorated) warranty.

Y___N___

TOUCH UP PAINT

A container with touch-up paint shall be provided with each truck. The container shall have a small touch-up brush that is attached to the top of the container.

Y___N___

DISSIMILAR METALS

The body and components shall be thoroughly protected against corrosion and/or oxidation caused by contact between dissimilar metals. These areas shall be protected by the use of corrosion resistant primers, gaskets and "ECK" (electrolic corrosion material) or any equivalent material.

CLARE FIRE DEPARTMENT

Y__N__

BODY UNDERCOATING

Undercoating of the apparatus body shall conform to the following;

- The rubberized undercoating shall be black in color and uniform in texture.
- The underside (chassis frame rails downward) of the apparatus body shall be sprayed with rubberized undercoating.
- The wheel well sections of the apparatus will be undercoated completely (above and below the chassis frame rail).
- The undercoating shall have corrosion-preventative properties.
- The undercoating material shall contain no asbestos.

Y__N__

LETTERING

Lettering will be provided by the manufacturer as follows:

Per customer design
3-1/2" shaded letters / numbers
Sixty (60) character allowance

Lettering shall be provided on the cab doors and/or body, Scotchlite material shaded in black.

Y__N__

DEPARTMENT LOGO/EMBLEM

One set of department logo will be supplied with the truck and put on front doors of chassis unless otherwise specified or approved.

Y__N__

NFPA BODY STRIPE

A 6" body stripe of white reflective is to be furnished around the entire apparatus with the exception of the wheel wells, pump panels, grille and rear of the apparatus over the chevron material.

Straight pattern chassis and body

Y__N__

CHEVRON STRIPING - REAR

Chevron striping shall be applied to the entire rear wall of the apparatus body. The chevrons shall consist of 6" wide Diamond Grade reflective striping at 45 degree angles from the tailboard in an inverted "V" pattern. The stripes shall alternate red reflective, lime reflective, red reflective, etc.

CLARE FIRE DEPARTMENT

Y__N__

WELDON VMUX MULTIPLEXED ELECTRICAL SYSTEM

The apparatus body will be a continuation of the Spartan supplied Weldon VMUX electrical system that accommodates the needs of the apparatus as presented in the chassis section of our proposal.

All electrical equipment installed by the apparatus builder shall conform to current automotive electrical system standards and the latest standards as outlined in NFPA #1901.

All electrical wire installed by the apparatus builder shall be rated to carry 125 percent of the maximum current for which the circuit is protected. A high-temp automotive primary wire that is insulated with chemically cross-linked Polyethylene and withstands prolonged temperatures of up to 350 degrees F. without melting or fusing shall be used. Wire shall be highly resistant to grease, oil, acids, brake fluid and abrasion. Wire shall meet or exceed S.A.E. specifications J1127.

Electrical connections in exposed areas outside of the cab shall be made using heat shrink or weather-proof connections. All connections shall have a corrosion preventative compound applied to them. All weather exposed lights shall have the sockets coated with this same compound.

Wire shall be individually color coded and be labeled every six (6") inches on the insulation. Wiring installed by body builder shall be run in a heat protective loom that is held in place with a rubber coated bracket that is fastened in place with stainless steel screws.

There will be nodes that will be used as test points and for service. The location of these points will be in the apparatus cab and in an enclosed box recessed into the side or back wall of a rear compartment. All wire connections shall be protected to promote a lasting, corrosion-free connection. All exterior terminal blocks will be installed in a weather resistant box. All wire harnesses will be easily accessible and replaceable.

Y__N__

12-V NFPA TEST

The following NFPA 9-14 test requirements shall be performed:

- Reserve capacity test
- Alternator test at idle
- Alternator test at full load
- Low voltage alarm test

Y__N__

CLEARANCE LIGHTS AND REFLECTORS

Clearance lights and reflectors shall be installed to meet current DOT standards and include:

- Two (2) Red LED marker lights
- Four (4) Red reflectors
- Two (2) Amber reflectors
- One (1) Red LED three-light cluster under the rear step.

CUSTOM PUMPER

CLARE FIRE DEPARTMENT

AUXILIARY TURN / RUNNING LIGHT

Y__N__

Two (2) auxiliary LED amber marker/turn lights shall be mounted just forward of rear axle, in the rear wheel well area. The lights shall be wired into the chassis light system and shall be flush mounted within a rubber grommet.

STOP/TAIL, TURN AND BACKUP LIGHTS

Y__N__

Whelen M6 series lights shall be installed at the rear of the apparatus as follows:

- Red LED stop/tail light, one (1) each side
- Amber LED turn light, one (1) each side
- Clear LED backup light, one (1) each side

Each shall be installed inside a one-piece housing, one each side. The lower rear warning light shall be included in the 4 light housing.

REAR LOWER LIGHTS BEZEL COLOR

Y__N__

The surface mounted lower stop/tail/turn and back up lights shall include chrome bezels.

LICENSE LIGHT AND BRACKET

Y__N__

A polished aluminum LED license plate light and bracket shall be installed on the rear of the vehicle.

LED PUMP GROUND LIGHTS (2)

Y__N__

Under body lighting will be provided for the apparatus pump module. Two (2) LED strip lights with clear lenses will be mounted below the runningboards, one (1) each side. The lights will be controlled by the parking brake switch.

LED BODY GROUND LIGHTS (4)

Y__N__

Under body lighting will be provided for the apparatus body. Four (4) LED strip lights with clear lenses will be mounted below the apparatus body, one (1) under each full height compartment. The lights will be controlled by the parking brake switch.

LED REAR TAILBOARD / BUMPER GROUND LIGHTS (2)

Y__N__

Under tailboard/bumper lighting will be provided for the rear of the apparatus. Two (2) LED strip lights with clear lenses will be angle mounted below the rear tailboard/bumper. The lights will be controlled by the parking brake switch.

CLARE FIRE DEPARTMENT

RECESSED STEP LIGHTS - LED

Y__N__

There shall be LED recessed step lights mounted in such a manner as to light the area around the runningboards, tailboard, and rear intermediate step.

ACCESS LADDER STEP LIGHTS - LED

Y__N__

There shall be three (3) Whelen LED step lights mounted in such a manner as to light the area around the access ladder. The light shall be recess mounted in a rubber grommet or surface mounted in a chrome bezel.

PUMP SERVICE LIGHT

Y__N__

There shall be a LED light with clear lens mounted inside the pump compartment to provide sufficient lighting.

COMPARTMENT DOOR SWITCHES

Y__N__

All exterior compartment doors will be provided with a door switch that shall activate the "Door Ajar" indicator light.. The switch shall be installed not to interfere with loading or unloading the equipment stored within the compartment.

DOOR AJAR INDICATOR

Y__N__

There shall be a red flashing door-ajar indicator located on the cab in easy view of the driver. The light shall be illuminated automatically whenever the apparatus parking brake is released and the following conditions exist:

- Any passenger or equipment door is open.
- Any ladder or equipment rack is not in the stowed position.
- The aerial stabilizer system not in its stowed position.
- Powered light tower is extended.
- Any other device is opened, extended or deployed that creates a hazard, or is likely to cause damage to the apparatus if it is moved.

HOSEBED LIGHTS

Y__N__

A LED strip light shall be installed to light the hosebed. The light shall be activated by the park brake switch. The light shall be protected and be mounted at the front of the hosebed.

CLARE FIRE DEPARTMENT

Y__N__

SIDE SCENE LIGHTS

The front upper body sides include two (2) Whelen model Pioneer PCPSM2(x) surface mount lights installed, one (1) on each side of the body.

The 154 watt +12v DC dual Pioneer lighthouse shall incorporate Super-LED® combination flood/spot light installed in ABS Cycholac™ resin surface mount housing. The surface mount housing will be chrome plated. The PCPSM2 configuration shall consist of 24 white Super-LEDs for the spot light with a specialized spot reflector on the bottom, 48 white Super-LEDs in the flood light with a clear optic collimator/metalized reflector assembly on the top, and a clear non-optic polycarbonate lens. The Pioneer flood/spot light shall have 16,000 usable lumens. The PCPSM2 new combination optic design projects light directly down at 5° and producing illumination to the side of the vehicle arching upward to a 90° pattern of light.

Y__N__

SIDE SCENE LIGHTS

The rear upper body sides include two (2) Whelen model Pioneer PCPSM2(x) surface mount lights installed, one (1) on each side of the body.

The 154 watt +12v DC dual Pioneer lighthouse shall incorporate Super-LED® combination flood/spot light installed in ABS Cycholac™ resin surface mount housing. The surface mount housing will be chrome plated. The PCPSM2 configuration shall consist of 24 white Super-LEDs for the spot light with a specialized spot reflector on the bottom, 48 white Super-LEDs in the flood light with a clear optic collimator/metalized reflector assembly on the top, and a clear non-optic polycarbonate lens. The Pioneer flood/spot light shall have 16,000 usable lumens. The PCPSM2 new combination optic design projects light directly down at 5° and producing illumination to the side of the vehicle arching upward to a 90° pattern of light.

Y__N__

REAR SCENE LIGHTS

The rear of the body shall include (2) Whelen model Pioneer PCPSM1(x) surface mount lights installed, one (1) on each side.

The 76 watt +12v DC single Pioneer lighthouse shall incorporate Super-LED® combination flood/spot light installed in ABS Cycholac™ resin surface mount housing. The surface mount housing will be chrome plated. The PCPSM1 configuration shall consist of 12 white Super-LEDs for the spot light with a specialized spot reflector on the bottom, 24 white Super-LEDs in the flood light with a clear optic collimator/metalized reflector assembly on the top, and a clear non-optic polycarbonate lens. The Pioneer flood/spot light shall have 7,800 usable lumens. The PCPSM1 new combination optic design projects light directly down at 5° and producing illumination to the side of the vehicle arching upward to a 90° pattern of light.

Y__N__

SCENE LIGHTING BEZEL COLOR

The surface mounted scene lights shall include chrome bezels.

CLARE FIRE DEPARTMENT

SCENE LIGHTING SWITCHING

Y__N__

The body and/or cab mounted scene lights shall include switches in the cab. Each side of the apparatus will include its own switch if applicable.

SCENELIGHT BACKUP RELAY

Y__N__

A relay will be provided in the rear scene light circuit to allow automatic use of the lights when the vehicle is placed in reverse.

HOUSEHOLD DUPLEX RECEPTACLE- SHORE POWER

Y__N__

There shall be eight (8) 120-volt/20 amp household duplex receptacle(s) mounted as directed by the Fire Department. A hinged weatherproof cover shall be installed over any exterior mounted receptacle(s).

Location(s): Back of doghouse, L1, L2, L3, B, R1, R2, R3

12-V POWER POINT - CONSTANT POWER - FUSE BLOCK

Y__N__

There shall be one (1) 12-volt constant power 6-position Blue-Sea fuse block with ground bar and cover installed as directed by the Fire Department.

Location(s): L1

BACKUP CAMERA WIRING AND ADDITIONAL WATERPROOF MONITOR

Y__N__

Wiring and a weather shield shall be supplied for the chassis supplied backup camera. The camera shall be installed below the hosebody handrail, rear step or some other mechanism to prevent damage.

An additional monitor shall be supplied and mounted on the pump panel. The monitor shall be water proof.

NFPA WARNING LIGHTS

Y__N__

The optical warning system on the fire apparatus shall be capable of two separate signaling modes during emergency operations. One mode shall signal that the apparatus is responding to an emergency and is calling for the right of way. The other mode shall signal that the apparatus is stopped and is blocking the right of way.

The switching for the two different modes shall be through switches and relays that sense the position of the parking brake.

CLARE FIRE DEPARTMENT

Y__N__

REAR WHEEL WELL WARNING LIGHTS

The rear wheel wells shall include two (2) Whelen 500 Series TIR6™ Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn. The lights shall be recess mounted within a rubber grommet kit.

The warning lights shall be red.

Y__N__

REAR TAILBOARD SIDE WARNING LIGHTS

The rear tailboard shall include two (2) Whelen M6 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn. The lights shall be mounted within a cast housing located on the top of the tailboard sides.

The warning lights shall be red.

Y__N__

FRONT UPPER BODY SIDE WARNING LIGHTS

The front upper body sides shall include two (2) Whelen M9 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the apparatus within a bezel.

The warning lights shall be red.

Y__N__

REAR UPPER BODY SIDE WARNING LIGHTS

The rear upper body sides shall include two (2) Whelen M9 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the apparatus within a bezel.

The warning lights shall be red.

Y__N__

UPPER REAR WARNING LIGHTS

The upper rear of the apparatus shall include two (2) Whelen M9 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the apparatus within a bezel.

The warning lights shall be red.

CLARE FIRE DEPARTMENT

Y__N__

LOWER REAR WARNING LIGHTS

The lower rear of the apparatus shall include two (2) Whelen M6 Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the apparatus within a bezel.

The warning lights shall be red.

Y__N__

WARNING LIGHTING BEZEL COLOR

The body and/or cab surface mounted warning lights shall include chrome bezels.

Y__N__

WARNING LIGHTING LENS COLOR

The body and/or cab surface mounted warning lights shall include colored lenses to match the warning light color.

Y__N__

WARNING LIGHTING SWITCHING

The body and/or cab mounted warning lights shall include switches in the cab. Each side of the apparatus will include its own switch if applicable.

A master warning light switch shall also be included.

Y__N__

FEDERAL Q2B SIREN - CUSTOMER SUPPLIED

A customer supplied pedestal style Federal Q2B siren shall be recess mounted in the front bumper. A recess kit shall be provided and supplied by the manufacturer.

Y__N__

SIREN SWITCH - FLOOR MOUNTED

There shall be a floor mounted foot siren switch to operate the mechanical siren. The switch shall be mounted and located as directed. There shall be a rocker switch located on the switch console for the mechanical siren brake control.

Y__N__

APPARATUS WARRANTY - TWO YEARS

The completed apparatus shall be warranted to be free from defects in workmanship and materials under normal use and service for a period of two (2) years from the date of delivery to the Fire Department. This warranty shall cover the costs for parts and labor for this period of time.

CLARE FIRE DEPARTMENT

ROOF LADDER

Y__N__

One (1) Duo Safety Model 775-A, 14 foot aluminum roof ladder shall be provided on the apparatus. The ladder shall be equipped with folding steel roof hooks on one end and steel spikes on the other end. The ladder shall meet or exceed all latest NFPA Standards.

EXTENSION LADDER

Y__N__

One (1) Duo-Safety Model 900-A, 24 foot two-section aluminum extension ladder shall be provided on the apparatus. The ladder shall meet or exceed all the latest NFPA standards.

FOLDING LADDER

Y__N__

One (1) Duo Safety Model 585-A, 10 foot folding aluminum ladder shall be provided on the apparatus. The ladder shall meet or exceed all the latest NFPA Standards.

PIKE POLE

Y__N__

One (1) Duo Safety 6' pike pole with round handle shall be provided on the apparatus. The pike pole shall be of fiberglass construction.

PIKE POLE

Y__N__

One (1) Duo Safety 8' pike pole with round handle shall be provided on the apparatus. The pike pole shall be of fiberglass construction.

SUCTION HOSE

Y__N__

Two (2) 6" x 10 foot lengths of AWG flexible suction hose shall be provided and equipped with lightweight couplings.

STRAINER

Y__N__

The low level strainer shall be department supplied.

CLARE FIRE DEPARTMENT

WHEEL CHOCKS

Y__N__

One (1) pair of Worden model HWG Grip-Lock aluminum wheel chocks shall be mounted on the apparatus. They shall be mounted in model U815 slide-out brackets.

WHEEL CHOCKS LOCATION

Y__N__

The wheel chocks shall be mounted fore of the rear axle on bottom side of the lower compartments.

SPANNER WRENCHES WITH HOLDER

Y__N__

An Akron Brass Style 2443, item 24430001 spanner wrenches with holder shall be provided. It shall be constructed of impact resistant nylon. The unit shall include two (2) Style 10 wrenches and one (1) Style 15 hydrant wrench.

Location: Rear of body

PURCHASER'S RESPONSIBILITY

Y__N__

These specifications are as complete, accurate and up to date as possible; however, it is the purchaser's responsibility for the safe, legal operation and maintenance of this apparatus and equipment.

DELIVERY PREP

Y__N__

The apparatus shall be detailed and cleaned prior to delivery.

All metal edges shall be carefully sanded and rounded. All compartment and exterior sheeting seams shall be carefully caulked.

Any loose equipment shall be stored on the truck.